

EUROLITE LED KKL-50 Floodlight 4100K silver

50 W LED floodlight with extension arm and screw terminal for fixation

Art. No.: 41600470

GTIN: 4026397603248



List price: 141.61 €

incl. 19% VAT.

Description:

The Eurolite KKL-50 LED floodlight illuminates trade fair booths, shop windows, workshops and even weatherproof outdoor areas.

You can purchase the KKL-50 in three simple casing colors: black, white and silver.

Features:

- Unique design
- For tabletops with up to 40 mm strength
- 1 powerful LED 50 W COB (chip-on-board) neutral white (NW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Easy installation
- With a beam angle of 75°
- Very high color rendering index (CRI)
- Various versions available
- Silent operation
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting
- Application possibility: Suspended; Wall mounting

Package contents

- 1 x spotlight, 1 x knurled screw, 1 x plate, 1 x user manual

Logistic

EAN / GTIN: 4026397603248

Weight: 2,36 kg

Length: 0.65 m

Width: 0.21 m

Height: 0.11 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

| | |
|----------------------------------|--|
| Power consumption: | 50 W |
| IP classification: | IP20 |
| Power connection: | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 1,0 mm ² H05RN-F |
| Cable length: | Approx. 0,8 m |
| Lamp type: | LED lamp |
| LED: | 1 x 50 W COB (chip-on-board) neutral white (NW) |
| Color temperature: | 4100K |
| Cooling: | Passive convection cooling |
| Control: | Plug and play |
| Setup: | Easy installation |
| Beam angle: | 75° |
| Beam angle (1/2 peak): | 75° |
| Beam angle (1/10 peak): | 125° |
| Color rendering index (CRI): | 90 Ra |
| Luminous flux: | 3769 lm |
| Housing color: | Silver |
| Dimensions: | Length: 64 cm Width: 20,5 cm Depth: 8,5 cm |
| Weight: | 2 kg |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | G |