

## EUROLITE LED CSL-320 Spotlight 6000K black

Bright, cold white spotlight, narrow beam angle and 32 x 10 W LED

Art. No.: 41600500

GTIN: 4026397588989



### Features:

- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Functions: dimmer, strobe
- Dimmer speeds (step response) adjustable via DMX
- Equipped with 32 x 10 W LED
- Color temperature 6000 K
- Mounting bracket for installation on a stand or a crossbeam
- Locking possibility at the mounting bracket
- Barndoors included in delivery
- Power connection via P-Con jack and included power cable with safety plug
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 6 devices
- 32 LEDs 10 W SMD 5050 cold white (CW)
- CREE LED installed
- Control via stand-alone; DMX
- Fixtures available for LED PC-Control 512
- With a beam angle of 7°

### Logistic

EAN / GTIN: 4026397588989

Weight: 9,00 kg

Length: 0.30 m

Width: 0.30 m

Height: 0.48 m

### Technical specifications:

Power consumption:	240 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)

Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	32 x 10 W SMD 5050 cold white (CW)
LED manufacturer:	CREE
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512
Beam angle:	7°
Beam angle (1/2 peak):	7°
Beam angle (1/10 peak):	17°
Color temperature:	6000K
Housing color:	Black
Dimensions:	Width: 23.5 cm Depth: 21 cm Height: 25 cm
Weight:	8.30 kg
Power supply:	100-240 V, 50/60 Hz
DMX channels:	3
DMX connection:	3-pol. XLR
LED type:	10 W
LED number:	32
Color temperature:	6000 K
Beam angle:	7°
Dimensions:	395 x 265 x 380 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### Scope of delivery:

---