

EUROLITE LED Theatre COB 100 UV

LED theatre spot with ultra violet (UV) 100 W COB (chip-on-board) LED

Art. No.: 41602020

GTIN: 4026397702378



List price: 296.31 €

incl. 19% VAT.

Features:

- 1 powerful LED 100 W COB (chip-on-board) ultra violet (UV)
- Dimmer electronic
- UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Preprogrammed in Light´J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 40°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397702378

Weight: 3,10 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.34 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 85 W

IP classification: IP20

| | |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 1 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 100 W COB (chip-on-board) ultra violet (UV) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 1; 4 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional) |
| Preprogrammed in: | Light´J; Light Captain; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 40° |
| Beam angle (1/2 peak): | 40° |
| Beam angle (1/10 peak): | 70° |
| Illuminance in Lux (lx): | Ultra violet (UV) 1m: 38 lx, 3m: 6 lx, 6m: 2 lx |
| Wavelength: | Ultra violet (UV) 402 nm |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 24,3 cm Depth: 31,1 cm Height: 32,0 cm |
| Weight: | 2,75 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |