

EUROLITE LED Theatre COB 200 WW/CW

LED theatre spot with 2in1 BCL CW/WW W COB (chip-on-board) LED

Art. No.: 41602034

GTIN: 4026397686548



Features:

- 1 LED COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light´J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 17°
- Variable color temperature 2500 K - 5700 K
- Very high color rendering index (CRI)
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397686548

Weight: 4,96 kg

Length: 0.45 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

| | |
|------------------------------|---|
| Power consumption: | 150 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 1 x COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 4; 5; 7 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light J; Light Captain; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 17° |
| Beam angle (1/2 peak): | 17° |
| Beam angle (1/10 peak): | 35° |
| Color temperature: | 2500K - 5700K adjustable |
| Color rendering index (CRI): | 98 Ra |
| Housing color: | Black matte |
| Attachment system: | Double bracket |
| Display type: | LCD display |
| Material: | Aluminum casting |
| Dimensions: | Width: 25.95 cm Depth: 20.00 cm Height: 37.65 cm |
| Weight: | 4.11 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise- sensitive environments) |
| Photobiological safety: | Risk Group 0 |
| Diameter mounting holes: | 3 x Ø11mm |
| Material: | Metal, 2.5 mm |
| Cable construction: | 3 x 1.0 mm ² H05VV-F |
| Cable length: | Approx. 1.2 m |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

- 1 x device
- 1 x power cord
- 1 x remote control
- 1 x user manual