eurolite®

EUROLITE LED THA-40PC Theater Spot bk

Fanless PC spot (DMX), warm white 57 W LED, color rendering index (CRI) >90

Art. No.: 41602080 GTIN: 4026397565218









List price: 374.85 €

incl. 19% VAT.

Features:

- 1 powerful LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Preprogrammed in LED PC-Control 512; Light J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 11° 48°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Silent operation
- For application areas such as: Trade fair and shop fitting; installation; stage; theater
- Application possibility: Suspended; on stand
- Package contents
- 1 x spotlight, 1 x barndoor, 1 x filter frame, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397565218 Weight: 4,30 kg Length: 0.36 m Width: 0.21 m Heigth: 0.27 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I	
Power connection:	Fixed power supply cord with safety plug	
Fuse:	5 x 20 mm, T 1 A fuse replaceable	
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)	
DMX channels:	1; 2	
DMX input:	3-pin XLR (M) mounting version	
DMX output:	3-pin XLR (F) mounting version	
Cooling:	Passive convection cooling	
Control:	Stand-alone; DMX	
Preprogrammed in:	LED PC-Control 512; Light J; Light Captain; Colorchief	
Projection:	Flicker-free	
Beam angle:	11° - 48°	
Beam angle (1/2 peak):	11 - 37°	
Beam angle (1/10 peak):	17 - 48°	
Color temperature:	3100K	
Color rendering index (CRI):	91 Ra	
Illuminance in Lux (lx):	Narrow 3m: 1656 lx, 6m: 424 lx Wide 3m: 348 lx, 6m: 103 lx	
Housing color:	Black	
Attachment system:	Mounting bracket	
Display type:	LCD display	
Transport aid:	Rubber feet	
Material:	Aluminum casting	
Slot for spot length:	13,1 cm x 13,1 cm	
Dimensions:	Length: 27,5 cm Width: 20,5 cm Depth: 25 cm	
Weight:	3,85 kg	
Noise classification:	Class 0 (no noise at all)	
Mounting bracket		
Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm	
Material:	Metal, 3 mm	
Power cord		
Cable construction:	3 x 0,75 mm² H05VV-F	
Cable length:	Approx. 1 m	
Barndoor		
Material:	Aluminum, 1,5 mm; metal	
Ring diameter:	Outside: 12,9 mm Inside: 10,9 mm	
Filter frame		
Diameter mounting holes:	1 x Ø4mm	
Shape:	Octagonal	
Material:	Aluminum, 0,8 mm	
Dimensions:	Width: 13 cm Height: 13 cm	

Diameter:	Ø	10,	5	cm

Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting