

EUROLITE LED THA-60PC Theater Spot

Spot with 60 W COB LED (RGBW) and plano-convex lens, extremely quiet, DMX

Art. No.: 41602110 GTIN: 4026397566604









List price: 427.21 €

incl. 19% VAT.

Features:

- With plano-convex lens
- Compact design
- 1 powerful LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- Preprogrammed in Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 7° 48°
- With mounting bracket
- LCD display
- Very quiet working noise
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x barndoor, 1 x user manual, 1 x filter frame

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W

Logistic

EAN / GTIN: 4026397566604

Weight: 4,19 kg Length: 0.36 m Width: 0.21 m Heigth: 0.27 m

(homogenous color mix) DMX channels: 5; 6; 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4;	IP classification:	IP20
(homogenous color mix) DMX channels: 5; 6; 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Capta Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Power connection:	Fixed power supply cord with safety plug
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4xt LED EASY OPERATOR 4xt; LED EASY OPERATOR DELUXE; Light Capta Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	LED type:	1 x 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Capte Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/12 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	DMX channels:	5; 6; 7
Cooling: Temperature-controlled fan Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x¢ LED EASY OPERATOR 4x¢ LED EASY OPERATOR DELUXE; Light Capta Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	DMX input:	1 x 3-pin XLR (M) mounting version
Control: Stand-alone; DMX Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Capta Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	DMX output:	1 x 3-pin XLR (F) mounting version
Preprogrammed in: Light'J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Capta Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Cooling:	Temperature-controlled fan
OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Capta Colorchief Projection: Flicker-free Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Control:	Stand-alone; DMX
Beam angle: 7° - 48° Beam angle (1/2 peak): 7 - 39° Beam angle (1/10 peak): 14 - 48° Housing color: Black Attachment system: Mounting bracket Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Preprogrammed in:	OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain;
Beam angle (1/2 peak): To - 39° Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Projection:	Flicker-free
Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Beam angle:	7° - 48°
Housing color: Attachment system: Mounting bracket LCD display Display type: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Beam angle (1/2 peak):	7 - 39°
Attachment system: Display type: LCD display Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Beam angle (1/10 peak):	14 - 48°
Display type: LCD display Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Housing color:	Black
Dimensions: Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Attachment system:	Mounting bracket
Width: 19,6 cm Depth: 17,3 cm Weight: 3,74 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Display type:	LCD display
Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Dimensions:	Width: 19,6 cm
sensitive environments)	Weight:	3,74 kg
Legal specifications	Noise classification:	· · ·
	Legal specifications	
Special product: Not designed for household room illumination	Special product:	Not designed for household room illumination
Intended use: Show effect lighting	Intended use:	Show effect lighting