

EUROLITE LED THA-100F MK3 Theater-Spot

Fresnel spotlight (fresnel lens), 100 W warm white LED, CRI >90, quiet, DMX

Art. No.: 41602127

GTIN: 4026397690453



List price: 653.31 €

incl. 19% VAT.

Features:

- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
 - Strobe effect
 - The device is cooled by low-noise cooling fan
 - Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Flicker-free
 - With a beam angle of 8° - 55°
 - Very high color rendering index (CRI)
 - With Mounting bracket
 - LCD display
 - Dimmer electronic; dimmer curves with adjustable response; pulse-width modulation variable; Dimmer speed (step response) adjustable
 - Preprogrammed in Light Captain
 - Rubber feet
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Trade fair and shop fitting; Installation; Stage; theater
 - Very quiet working noise
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x barn door, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397690453

Weight: 9,30 kg

Length: 0.49 m

Width: 0.40 m

Height: 0.38 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

| | |
|----------------------------------|---|
| Power consumption: | 95 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version included |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 1 x 100 W COB (chip-on-board) warm white (WW) |
| Color temperature: | 3000K |
| Flash rate: | 20 Hz |
| DMX channels: | 1; 3 |
| DMX input: | 3-pin XLR (M) mounting version 5-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version 5-pin XLR (F) mounting version |
| Cooling: | Low-noise cooling fan |
| Control: | Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 8° - 55° |
| Beam angle (1/2 peak): | 8 - 40° |
| Beam angle (1/10 peak): | 16 - 55° |
| Color rendering index (CRI): | 96 Ra |
| Luminous flux: | 5384 lm |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Transport aid: | Rubber feet |
| Material: | Aluminum casting; metal |
| Dimensions: | Length: 35,0 cm Width: 31,5 cm Height: 39,5 cm |
| Weight: | 7,15 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Energy efficiency class (A - G): | G |
| Power cord | |
| Cable construction: | 3 x 1,5 mm ² H05VV-F |
| Cable length: | Approx. 1,8 m |
| Mounting bracket | |
| Diameter mounting holes: | 5 x Ø13mm |
| Material: | Aluminum casting, 6 mm |
| Barndoor | |

| | |
|----------------|--|
| Material: | Aluminum, 1 mm |
| Ring diameter: | Outside: 172 mm Inside: 150 mm |
| Dimensions: | Width: 42,2 cm Height: 42,5 cm |
| Filter frame | |
| Material: | Aluminum, 1 mm |
| Dimensions: | Width: 18,5 cm Height: 18,5 cm Diameter: Ø 15,2 cm |