

EUROLITE LED THA-120PC Theater-Spot

Fresnel spotlight (fresnel lens), 120 W COB LED (RGBW), extremely quiet, DMX

Art. No.: 41602130

GTIN: 4026397578447



List price: 712.81 €

incl. 19% VAT.

Features:

- Compact design
- 1 powerful LED 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; Sound to light via Microphone
- Flicker-free
- With a beam angle of 3° - 43°
- With Mounting bracket
- Preprogrammed in LED PC-Control 512; Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Installation; Trade fair and shop fitting; Stage; theater; Rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame

Logistic

EAN / GTIN: 4026397578447

Weight: 6,60 kg

Length: 0.49 m

Width: 0.32 m

Height: 0.32 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 135 W

IP classification: IP20

Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
LED:	1 x 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	3° - 43°
Beam angle (1/2 peak):	3 - 32°
Beam angle (1/10 peak):	9 - 43°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 37 cm Width: 25,6 cm Depth: 36 cm
Weight:	5,85 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting