

EUROLITE Audience Blinder 2x100W LED COB WW

Audience blinder with 2x 100 W COB LED, warm white

Art. No.: 41604121

GTIN: 4026397672176



Description:

Warm white audience blinder

The Audience Blinder from EUROLITE is equipped with 2x100W COB LEDs in warm white. The Audience Blinder is particularly suitable for use at concerts as well as at festivals or in theatres and on catwalks. The swivelling mounting bracket is included in delivery.

You can control each COB LED individually in static mode. The color temperature is 3100 K. In automatic mode you can use nine integrated show programs, furthermore control via DMX (also wireless via QuickDMX) is possible. The P-Con mains connections allow you to easily connect up to eight devices in series. A further advantage of the Audience Blinder is the stroboscopic effect with variably adjustable speeds.

Addressing and settings can be made using the integrated control unit with LCD display.

Logistic

EAN / GTIN: 4026397672176

Weight: 5,79 kg

Length: 0.45 m

Width: 0.18 m

Height: 0.28 m

Features:

- DMX and power terminals intelligently designed for easy wiring
- 2 LEDs 100 W COB (chip-on-board) warm white (WW) LEDs controlled separately
- Strobe effect
- 9 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain; Light J
- Flicker-free
- With a beam angle of 70°
- Very high color rendering index (CRI)

- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; theater; rental
- Application possibility: Suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	2 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 6
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMV by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; Light J
Projection:	Flicker-free
Beam angle:	70°
Beam angle (1/2 peak):	70°
Color temperature:	3100K
Color rendering index (CRI):	97 Ra
Wavelength:	632 nm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Material:	Metal
Dimensions:	Width: 41 cm Depth: 15.3 cm Height: 22.4 cm
Weight:	5.22 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	3 x Ø11mm

Material:	Metal, 4 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual