

EUROLITE Audience Blinder 2x100W LED COB 3200K

Audience blinder, wide beam 2 x 100 W COB LED (warm white)

Art. No.: 41606120

GTIN: 4026397455243



The article is no longer in our assortment.

Features:

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 2 powerful LEDs 100 W COB (chip-on-board) warm white (WW)
- Dimmer
- Strobe effect
- Control via DMX
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 60°

Logistic

EAN / GTIN: 4026397455243

Weight: 4,95 kg

Length: 0.47 m

Width: 0.20 m

Height: 0.29 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 260 W

IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	2 x 100 W COB (chip-on-board) warm white (WW)
Color temperature:	3200K
Flash rate:	1 - 20 Hz
Equipment:	Dimmer
DMX channels:	1; 2; 4
Control:	DMX
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Beam angle:	60°
Beam angle (1/2 peak):	60°
Housing color:	Black
Dimensions:	Width: 42 cm Depth: 14 cm Height: 24 cm
Weight:	4,50 kg
DMX channels:	1/2/4
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	2
LED type:	Array 100 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	140 x 420 x 240 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting