

## EUROLITE Multiflood IP 8x10W RGBW Wash

Silent IP65 LED floodlight with RGBW color mixing, diffuser cover, barn doors and IR remote control

Art. No.: 41606250

GTIN: 4026397724196



### Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 8 LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 36 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; IR remote control; RDM
- Fixtures available for Light Captain; LED PC-Control 512; Light´J; Colorchief
- Flicker-free
- With a beam angle of 10°
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Architecture; stage; wedding/gala/events; Trade fair and shop fitting; theater; rental
- Silent operation
- Application possibility: Suspended; on stand; standing
- 3 buttons on the remote control for saving your own settings

### Logistic

EAN / GTIN: 4026397724196

Weight: 7,10 kg

Length: 0.36 m

Width: 0.27 m

Height: 0.30 m

## Technical specifications:

|                         |                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                         |
| Power consumption:      | 80 W                                                                                           |
| IP classification:      | IP65                                                                                           |
| Protection class:       | Protection class I                                                                             |
| Power connection:       | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug (provided) |
| Power output:           | IP T-Con (F) mounting version                                                                  |
| Lamp type:              | LED lamp                                                                                       |
| LED type:               | 8 x 10 W SMD 5050 4in1 QCL RGBW<br>(homogenous color mix)                                      |
| Flash rate:             | 0.8 - 28 Hz                                                                                    |
| DMX channels:           | 3; 4; 6; 8; 11                                                                                 |
| DMX input:              | 3-pin XLR (M) mounting version IP                                                              |
| DMX output:             | 3-pin XLR (F) mounting version IP                                                              |
| Cooling:                | Passive convection cooling                                                                     |
| Control:                | Stand-alone; DMX; master/slave function; IR<br>remote control; RDM                             |
| Fixtures available for: | Light Captain; LED PC-Control 512; Light J;<br>Colorchief                                      |
| Projection:             | Flicker-free                                                                                   |
| Beam angle:             | 10°                                                                                            |
| Beam angle (1/2 peak):  | 10°<br>Frost filter 25°                                                                        |
| Beam angle (1/10 peak): | 25°<br>Frost filter 55°                                                                        |
| Housing color:          | Black                                                                                          |
| Attachment system:      | Mounting bracket<br>Omega bracket                                                              |
| Display type:           | OLED display                                                                                   |
| Theft protection:       | KENSINGTON LOCK                                                                                |
| Dimensions:             | Length: 31.9 cm<br>Width: 14 cm<br>Height: 24.8 cm                                             |
| Weight:                 | 6.10 kg                                                                                        |
| Noise classification:   | Class 0 (no noise at all)                                                                      |
| Battery:                | 1 x button cell 3.0 V CR2032 lithium manganese<br>built-in                                     |
| Special product:        | Not designed for household room illumination                                                   |
| Intended use:           | Show effect lighting                                                                           |

## Scope of delivery:

1 x device  
1 x user manual  
1 x power cord  
1 x remote control  
1 x battery

1 x frost filter  
1 x omega bracket  
1 x barndoor