

## EUROLITE LED IP Atmo Bar 10

Weather-proof blinder bar with pixel control and colored atmospheric light in the reflector

Art. No.: 41606410

GTIN: 4026397719611



**List price: 1069.81 €**

incl. 19% VAT.

### Features:

- 10 powerful LEDs 24 W COB (chip-on-board) CW/WW (homogenous color mix)<BR> LEDs controlled separately
- 200 powerful LEDs 0,2 W SMD 3528 3in1 TCL RGB (homogenous color mix)<BR>10 segments controlled separately
- Variable color temperature 1800 K - 6000 K
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response; white balance adjustable
- Strobe effect
- 10 integrated show programs
- The device is cooled by low-noise cooling fan
- Control via stand-alone; Master/slave function; DMX; ArtNet; RDM
- Preprogrammed in Light Captain; LED PC-Control 512
- Flicker-free
- With a beam angle of 28°
- With Mounting bracket; with Omega bracket
- OLED display
- Mains input and output for power linking up to 4 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Clubs/dancing school; Stage; Rental
- Very quiet working noise
- Application possibility: Suspended

### Package contents

- 1 x bar, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x xLR cable

### Logistic

EAN / GTIN: 4026397719611

Weight: 11,85 kg

Length: 1.10 m

Width: 0.28 m

Height: 0.25 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	315 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	10 x 24 W COB (chip-on-board) CW/WW (homogenous color mix) 200 x 0,2 W SMD 3528 3in1 TCL RGB (homogenous color mix)
Color temperature:	1800K - 6000K adjustable
DMX channels:	10; 14; 20; 50; 59
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Low-noise cooling fan
Control:	Stand-alone; Master/slave function; DMX; ArtNet; RDM
Preprogrammed in:	Light Captain; LED PC-Control 512
Projection:	Flicker-free
Beam angle:	28°
Beam angle (1/2 peak):	28°
Beam angle (1/10 peak):	63
Housing color:	Black
Attachment system:	Mounting bracket 2x Omega bracket
Display type:	OLED display
Connections:	2 x RJ-45 E-Con (F) mounting version
Dimensions:	Length: 1,01 m Depth: 12,5 cm Height: 24 cm
Weight:	10,50 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting