

EUROLITE AKKU Bar-6 QCL

Battery-powered LED bar with 4in1 LEDs and IR remote control

Art. No.: 41700122

GTIN: 4026397673364



List price: 332.01 €

incl. 19% VAT.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 6 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix) LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 35 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Master/slave function; Sound to light via Microphone; IR remote control; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
- Flicker-free
- With a beam angle of 8°
- With double bracket
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

Logistic

EAN / GTIN: 4026397673364

Weight: 4,27 kg

Length: 0.56 m

Width: 0.13 m

Height: 0.26 m

- 1 x bar, 1 x user manual, 1 x power cord, 1 x diffusor cover, 1 x remote control, 1 x battery

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 11,1 V, 10400 mAh, 115,44 Wh
Lamp type:	LED lamp
LED:	6 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 8; 11; 12; 13; 17; 24; 29
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Master/slave function; Sound to light via Microphone; IR remote control; W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	8°
Beam angle (1/2 peak):	8°
Beam angle (1/10 peak):	17°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Length: 50,2 cm Depth: 6 cm Height: 20,1 cm
Weight:	3,80 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting