

## EUROLITE AKKU B-40 Laser Beam Effect AIR

Art. No.: 41700340

Battery-powered LED beam effect with RGBW colors, RG laser, AirW wireless system (2.4 GHz) and RF remote control



### Features:

- Integrated AirW radio transceiver for wireless master/slave operation
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- 2 laser diodes project hundreds of red and green laser beams
- Cordless, flexible and versatile
- Battery operation up to 11h depending on program used
- Integrated automatic charging of the battery
- 5 LEDs 8 W SMD 9095 4in1 QCL RGBW<BR>3 segments controlled separately
- Dimmer electronic; color selection adjustable; program selection manual; Energy-saving mode adjustable; program speed adjustable; Rotation speed adjustable; Rotation direction adjustable
- Multi beam effect; laser; strobe effect
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- 7 integrated show programs
- Highly efficient air flow from front to rear
- The device is cooled by low-noise cooling fan at the base; cooling fan at the head
- Control via stand-alone; DMX; AirW; sound to light via microphone; master/slave function; wireless remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- DMX fail mode (blackout; hold; auto; full on)
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- Charge status indicator
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window

### Logistic

EAN / GTIN: 4026397741155  
Weight: 9,50 kg  
Length: 0.40 m  
Width: 0.43 m  
Height: 0.53 m

- Very quiet working noise
  - Application possibility: Standing; suspended
  - 3 buttons on the remote control for saving your own settings
- light effect**
- AirW: operating range up to 70m with line-of-sight
- remote control**
- Operating range up to 30m with line-of-sight

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Battery/battery pack built-in
Cable construction:	3 x 1.0 mm <sup>2</sup> H05VV-F
Power output:	1 x IEC connector (F) mounting version Bypass
Device fuse:	5 x 20 mm, T 2 A fuse replaceable
Battery pack type:	1 x lithium ion 18.5 V, 13000 mAh, 240.5 Wh
Battery pack:	Battery operation up to 11h depending on program used Recharging time 7h
Lamp type:	LED lamp
LED type:	5 x 8 W SMD 9095 4in1 QCL RGBW
Flash rate:	1 - 20 Hz
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 40 mW 532nm
DMX channels:	3; 10; 22
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version Bypass
Cooling:	1 x low-noise cooling fan at the base, air flow from front to rear 1 x cooling fan at the head
Control:	Stand-alone; DMX; AirW; sound to light via microphone; master/slave function; wireless remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Projection:	Flicker-free
DMX fail mode:	Blackout; hold; auto; full on
Housing color:	Black matte
Attachment system:	Omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Display:	Charge status indicator
Status LED:	Charge status indicator
USB port:	1 x type A

Material:	Metal, painted
Dimensions:	Length: 32 cm Width: 26 cm Height: 39 cm
Weight:	6.90 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Range:	AirW: range up to 70m with line-of-sight
Carrier frequency:	2.4 GHz
Material thickness:	3 mm
Battery:	1 x 12 V 23AE alkaline manganese built-in
Range:	Range up to 30m with line-of-sight
Carrier frequency:	433.92 MHz

### **Scope of delivery:**

- 1 x light effect
- 1 x power cord
- 1 x omega bracket
- 1 x user manual
- 1 x remote control
- 4 x screw
- 4 x washer
- 1 x declaration of conformity
- 1 x battery