

## EUROLITE AKKU IP UP-4 QCL Spot QuickDMX

Weather-proof (IP65), upright with 4 x 10 W 4in1 LED, QuickDMX & frost filter

Art. No.: 41700542

GTIN: 4026397629606



### Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable; colors preset
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; sound to light via microphone; IR remote control; master/slave function
- Fixtures available for Light´J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 7°
- With bracket for floor use
- LCD display
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing

### Logistic

EAN / GTIN: 4026397629606

Weight: 4,71 kg

Length: 0.22 m

Width: 0.22 m

Height: 0.23 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via IP P-Con (Power in) yellow mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1.2 m
Battery pack type:	1 x lithium ion 14.8 V, 7800 mAh, 115.44 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; sound to light via microphone; IR remote control; master/slave function
Fixtures available for:	Light J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	7°
Beam angle (1/2 peak):	7°
Beam angle (1/10 peak):	20°
Housing color:	Black
Attachment system:	Bracket for floor use
Display type:	LCD display
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 15 cm Depth: 18 cm Height: 19.8 cm
Weight:	4.44 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

---

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x frost filter
- 1 x remote control
- 1 x battery
- 2 x knurled screw
- 1 x mounting bracket
- 2 x screw
- 1 x declaration of conformity