

EUROLITE AKKU UP-7 QCL Spot QuickDMX

Uplight with 7 x 8 W 4in1 LED, QuickDMX transceiver, frost filter and IR remote control

Art. No.: 41700544

GTIN: 4026397670387



List price: 451.01 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- Sturdy metal housing with handle and folding foot for angled placement
- Cordless, flexible and versatile
- Battery operation up to 17h depending on program used
- Integrated automatic charging of the battery and status indicator
- 7 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance adjustable
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; sound to light via microphone; QuickDMX
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 9°
- Monochrome OLED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; rental
- Silent operation

Logistic

EAN / GTIN: 4026397670387

Weight: 4,00 kg

Length: 0.21 m

Width: 0.21 m

Height: 0.23 m

- Application possibility: Standing

Package contents

- 1 x device, 1 x power cord, 1 x remote control, 1 x battery, 1 x frost filter, 2 x knurled screw, 1 x declaration of conformity, 1 x user manual

Technical specifications:

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 70 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Battery/battery pack built-in |
| Cable length: | Approx. 1,2 m |
| Power output: | 1 x P-Con (gray), mounting version |
| Battery pack type: | 1 x lithium ion 25,9 V, 7800 mAh, 202,02 Wh |
| Battery pack: | Battery operation up to 17h depending on program used Recharging time 3,5h |
| Lamp type: | LED lamp |
| LED type: | 7 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 1 - 23 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; IR remote control; master/slave function; sound to light via microphone; QuickDMX |
| Preprogrammed in: | EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 9° |
| Beam angle (1/2 peak): | 9° |
| Beam angle (1/10 peak): | 18° |
| Housing color: | Black |
| Display type: | Monochrome OLED display |
| Transport aid: | Rubber feet |
| Theft protection: | KENSINGTON LOCK |
| Dimensions: | Width: 13,8 cm Depth: 16,7 cm Height: 18,9 cm |
| Weight: | 3,60 kg |
| Noise classification: | Class 0 (no noise at all) |

| | |
|----------------------|---|
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |