

EUROLITE AKKU IP UP-4 Plus HCL Spot WDMX

IP65 uplight with replaceable battery, RGBWA+UV LEDs, WDMX and IR remote control

Art. No.: 41700580

GTIN: 4026397657623



The article is no longer in our assortment.

Features:

- Quick and tool-free battery change, additional rechargeable battery optionally available
- Integrated W-DMX transceiver for wireless DMX Control
- Additional frost filter provides a wide, soft and homogeneous light
- Sturdy metal housing with handle and folding foot for angled placement
- Cordless, flexible and versatile
- Battery operation up to 9,5h depending on program used
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 10 W SMD 5050 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 49 integrated show programs
- Direct color selection for 63 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; W-DMX by wireless solution; master/slave function; sound to light via microphone; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- With a beam angle of 16°
- With bracket for floor use
- Rubber feet
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; rental

Logistic

EAN / GTIN: 4026397657623

Weight: 5,00 kg

Length: 0.27 m

Width: 0.27 m

Height: 0.26 m

- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x power cord, 1 x external mains adapter, 1 x remote control, 1 x frost filter, 2 x screw, 1 x plate, 1 x user manual, 1 x declaration of conformity, 1 x battery, 1 x battery pack

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12,6V DC 3000 mA
Pin configuration:	Inside + / outside -
Power consumption:	35 W
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Battery/battery pack
Battery pack type:	1 x lithium ion 11,1 V, 13000 mAh, 144,3 Wh
Battery pack:	Battery operation up to 9,5h depending on program used Recharging time 8h
Lamp type:	LED lamp
LED type:	4 x 10 W SMD 5050 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	6; 8; 12
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; W-DMX by wireless solution; master/slave function; sound to light via microphone; IR remote control
Preprogrammed in:	Light´J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Carrier frequency:	2,4 GHz
Beam angle:	16°
Beam angle (1/2 peak):	16°
Housing color:	Black
Attachment system:	Bracket for floor use
Transport aid:	Rubber feet
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 17,1 cm Depth: 13,8 cm Height: 20 cm
Weight:	4,50 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting