

EUROLITE AKKU IP PAR 7 QCL CRMX MK2

IP65 battery-powered spotlight with RGBW LEDs, CRMX, frost filters and IR remote control

Art. No.: 41700793

GTIN: 4026397727623



List price: 593.81 €

incl. 19% VAT.

Features:

- Integrated wireless receiver for CRMX operation
- Two additional frost filters provide a soft, homogeneous light
- Battery operation up to 9h depending on program used
- 7 powerful LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Emergency lighting function in case of power failure; color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance; Energy-saving mode
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; IR remote control; DMX; W-DMX by wireless solution; CRMX by LumenRadio; RDM
- Preprogrammed in Light'J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 6°
- With double bracket
- OLED display
- Display of the remaining battery life for the current setting
- Charge status indicator
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- Silent operation
- For application areas such as: Wedding/gala/events; stage; mobile use; rental

Logistic

EAN / GTIN: 4026397727623

Weight: 5,85 kg

Length: 0.23 m

Width: 0.24 m

Height: 0.34 m

- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x frost filter, 2 x knurled screw, 1 x declaration of conformity, 2 x mounting bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Power output:	1 x IP T-Con (F) mounting version
Battery pack:	Battery operation up to 9h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	7 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; master/slave function; IR remote control; DMX; W-DMX by wireless solution; CRMX by LumenRadio; RDM
Preprogrammed in:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	6°
Beam angle (1/2 peak):	6° Frost filter 13° Frost filter 20°
Beam angle (1/10 peak):	16° Frost filter 32° Frost filter 44°
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Display:	Battery runtime calculation , charge status indicator
Color:	Black
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 23,4 cm Height: 28,0 cm Diameter: Ø 17,0 cm

Weight:	5,30 kg
Noise classification:	Class 0 (no noise at all); Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting