

EUROLITE AKKU IP Tourlight 200 RGB+WW

Silent IP65 battery powered spotlight with RGB+WW color mixture, QuickDMX, CRI >90

Art. No.: 41700900

GTIN: 4026397705096



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 20h depending on program used
- 1 LED 200 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Dimmer electronic; color blend stepless
- 9 integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; IR remote control; master/slave function
- Fixtures available for Light Captain; Colorchief
- Flicker-free
- With a beam angle of 30°
- Variable color temperature 1800 K - 8000 K
- Very high color rendering index (CRI)
- With omega bracket; with double bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397705096

Weight: 6,30 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.39 m

Technical specifications:

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) power supply cord with safety plug (provided) |
| Power output: | IP T-Con (F) mounting version |
| Device fuse: | 5 x 20 mm, T fuse serviceable |
| Battery pack type: | 1 x lithium ion 22.2 V, 4400 mAh, 97.68 Wh |
| Battery pack: | Battery operation up to 20h depending on program used Recharging time 4.5h |
| Lamp type: | LED lamp |
| LED type: | 1 x 200 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 3; 4; 5; 6; 10 |
| DMX input: | 3-pin XLR (M) mounting version IP |
| DMX output: | 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; QuickDMX; IR remote control; master/slave function |
| Fixtures available for: | Light Captain; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 30° |
| Beam angle (1/2 peak): | 30° |
| Beam angle (1/10 peak): | 60° |
| Color temperature: | 1800K - 8000K adjustable |
| Color rendering index (CRI): | 93 Ra |
| Housing color: | Black |
| Attachment system: | Omega bracket Double bracket |
| Display type: | LCD display |
| Dimensions: | Width: 25.1 cm Depth: 27.2 cm Height: 32.7 cm Diameter: Ø 18.2 cm |
| Weight: | 5.85 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x remote control
- 1 x battery