# EUROLITE AKKU KLS-180 Compact Light Set

Complete DMX LED lighting system with rechargeable battery pack

**Art. No.: 41701000**

GTIN: 4026397676440

## List price: 439.11 €

incl. 19% VAT.

## Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Movable and tiltable spotlights
- Battery operation up to 20h depending on program used
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; Sound to light via Microphone; DMX; IR remote control; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 9°
- 4 digit 7-segment LED display
- For application areas such as: Band/rehearsal room; mobile djs / entertainer; Stage; small rental; mobile use
- Silent operation
- Preprogrammed in EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light´J
- Mains input and output for power linking up to 8 units
- Application possibility: On stand; suspended
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator

  **spotlight**
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)<BR> spots controlled separately

## Logistic

EAN / GTIN: 4026397676440

Weight: 7,20 kg

Length: 0.68 m

Width: 0.21 m

Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

**bar**

- 4 powerful LEDs 1 W high-power cold white (CW)<BR> LEDs controlled separately

**Package contents**

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x bag

## Technical specifications:

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP20 |
| Power connection: | Battery/battery pack<br>Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IEC connector (F) mounting version |
| Fuse: | T 1 A Fuse replaceable |
| Battery pack type: | 1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh |
| Battery pack: | Battery operation up to 20h depending on program used<br>Recharging time 5h |
| Lamp type: | LED lamp |
| DMX channels: | 3; 4; 8; 21 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; Sound to light via Microphone; DMX; IR remote control; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light´J |
| Projection: | Flicker-free |
| Beam angle: | 9° |
| Beam angle (1/2 peak): | 9° |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 61 cm<br>Depth: 14,5 cm<br>Height: 27,4 cm |
| Weight: | 5,90 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x  Button cell 3.0 V CR2025 lithium manganese built-in |
| Spotlight | |
| LED type: | 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Bar | |
| LED type: | 4 x 1 W high-power cold white (CW) |
| Flash rate: | 0 - 20 Hz |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Legal specifications

| | |
|---|---|
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.