

EUROLITE PAR-56 Spot Short with Cable sil

PAR-56 housing with silicone cable and open cable ends

Art. No.: 42000810 GTIN: 4026397357332











incl. 19% VAT.

Features:

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong cable tension relief
- The device is cooled by passive convection cooling
- With mounting bracket
- For PAR 56

Package contents

1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

Logistic

EAN / GTIN: 4026397357332

Weight: 0,95 kg Length: 0.20 m Width: 0.20 m Heigth: 0.27 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/500 W PAR-56
Power connection:	Fixed supply cord with open wires
Cable construction:	3 x 0,75 mm² H05SS-F
Cable length:	Approx. 0,8 m
Base:	GX16d

Lamp type:	Selectable
Color generation:	Via color filter frame
Cooling:	Passive convection cooling
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	21,4 cm x 21,8 cm
Dimensions:	Length: 26 cm Width: 23,5 cm Height: 22 cm
Weight:	0,80 kg
Mounting bracket	
Diameter mounting holes:	2 x Ø13mm
Material:	Metal, 2 mm
Filter frame	
Diameter mounting holes:	4 x Ø8mm
Shape:	Octagonal
Grid size:	10 x 10 mm
Material:	Aluminum, 0,6 mm
Dimensions:	Length: 21,5 cm Width: 21,5 cm Diameter: Ø 17,1 cm
Lamp clamping ring	
Material:	Steel, 4 mm
Color:	Silver
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting