

EUROLITE Audience Blinder 4xPAR-36 QCL LED bk

LED Audience Blinder with PAR-36 Blinder housing with RGBW LEDs (4in1)

Art. No.: 42103479

GTIN: 4026397443035



The article is no longer in our assortment.

Features:

- Equipped with 24 x 8 W QCLs (quadcolor LEDs) distributed in 4 segments
- Each segment can be controlled individually via DMX
- Sound-control via built-in microphone; sensitivity adjustable
- Functions: Static colors, RGBW color mixture, internal programs, dimmer and strobe settings via DMX, Master/Slave
- 4, 6 or 19 DMX channels selectable for numerous applications
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Swivelable lamp rows
- Rugged housing and an appealing design
- Comfortable addressing and setting via control panel with LCD display and four operating buttons
- Locking possibility at the mounting bracket
- DMX control via every standard DMX controller
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- Control via Sound to light via Microphone

Logistic

EAN / GTIN: 4026397443035

Weight: 14,05 kg

Length: 0.65 m

Width: 0.50 m

Height: 0.27 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 220 W

IP classification: IP20

Flash rate:	1 - 20 Hz
DMX channels:	4
Control:	Sound to light via Microphone
Beam angle (1/2 peak):	19°
Dimensions:	Width: 44,5 cm Depth: 19 cm Height: 56,5 cm
Weight:	11,95 kg
DMX channels:	4/6/19
DMX connection:	3-pin XLR
Flash-rate:	20 Hz
Sound-control:	via built-in microphone
LED type:	8 W QCL
LED number:	24
Beam angle:	19°
Dimensions (L x W x H):	190 x 445 x 565 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting