

EUROLITE KLS-Kombo Pack 7

Mobile light set with foot pedal

Art. No.: 42109547

GTIN:



Features:

- Combines four LED spots and four matrix effects
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109610 EUROLITE LED KLS-150 Compact lightset, 51918559 EUROLITE LED MAT-Bar 4x64 Matrix strip, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
 - KLS-150 Compact lightset
 - TCL LEDs for exquisite RGB mixing
 - Foot controller included
 - Transport bag
 - MAT-Bar 4x64 Matrix strip
 - Space-saving solution
 - Diverse mounting options; via mounting hole for example
 - 256 LEDs
 - You can find more information under the respective article
 - <p>EUROLITE LED KLS-150 Compact light set
 - <h2 class="featureSatz">Compact LED spotlight set with 16 3in1 LEDs</h2>Compact LED light set with 4 slimline spots, stand adaptor and foot pedal
 - Ultra-light ideally suited for mobile use
 - Mounts to stands and truss systems
 - Comes pre-assembled with practical transport bag
 - 4 tri-color LEDs per spot provide for an exquisite RGB color mix
 - Movable and tiltable spotlights
 - Automatic mode with preset colors and programs (RGB color change and fade)
 - Program speed adjustable
 - Sound-control via built-in microphone with sensitivity control

Logistic

- Blackout function
- Convenient control via supplied foot pedal FP-2
- Black lacquered metal version
- Ready for connection with power cord and safety plug
- <p>OMNITRONIC Speaker System Stand alu bk
- <h2 class="featureSatz">High-quality speaker stand</h2>Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height
- <p>EUROLITE STV-3529 Adapter long
- <h2 class="featureSatz">Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg</h2>For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot
- <p>EUROLITE LED MAT-Bar 4x64 Matrix bar
- <h2 class="featureSatz">Flower effect bar with 256 LEDs (RGB)</h2>DMX512 control via regular DMX controller (occupies 7 channels)
- The colorful flower beams change their direction of movement at every bass beat in sound controlled mode
- Sound controlled via built-in microphone
- Microphone sensitivity adjustable via rotary control
- Auto mode, speed adjustable via DMX
- Internal programs
- Master/Slave function
- Control panel with 4 buttons and LED display
- Rugged compact housing
- Ready for connection with power cord and plug
- Including mounting bracket and mounting hole (36 mm) with fixation screw for installation on a truss system or stand, and carry bag
- Control via stand-alone; DMX
- Fixtures available for Light'J
- <p>OMNITRONIC XLR Cable 3-pin 1m bk
- <h2 class="featureSatz">Audio cable with 3-pin XLR connectors</h2>

Technical specifications:

Weight:	17.33 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED KLS-150 Compact light set

Power supply:	230 V AC, 50 Hz
Power consumption:	60.00 W
Dimensions:	Width: 95 cm Depth: 4.5 cm Height: 23 cm
Weight:	5.80 kg
LED type:	3 W TCL
LED number:	16
Beam angle:	15°
Sound control:	via built-in microphone
Dimensions (L x W x H):	950 x 45 x 230 mm

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3.45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8.50 cm Depth: 5 cm Height: 19.50 cm
Weight:	1.50 kg

EUROLITE LED MAT-Bar 4x64 Matrix bar

Power supply:	230 V AC, 50 Hz
Power consumption:	40.00 W
IP classification:	IP20
Lamp type:	LED lamp
Control:	Stand-alone; DMX
Fixtures available for:	Light J
Beam angle (1/2 peak):	15°
Housing color:	Black
Dimensions:	Width: 80 cm Depth: 9 cm Height: 23 cm
Weight:	6.48 kg
DMX channels:	7

DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 mm
LED number:	256
Beam angle:	15°
Mounting hole:	D = 36 mm
Dimensions (L x W x H):	800 x 90 x 230 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC XLR Cable 3-pin 1m bk

Cable construction:	2 x 0.22 mm ² microphone cable
Cable length:	1 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Dimensions:	Diameter: Ø 0.60 cm
Weight:	0.10 kg
Material:	Metal

Scope of delivery:

1 x device
1 x user manual
2 x knurled screw