

EUROLITE KLS-Kombo Pack 14

Ultra bright mobile light set

Art. No.: 42109554

GTIN:



The article is no longer in our assortment.

Features:

Ultra bright mobile light set

- Combines four LED spots, two LED bars and one hybrid bar with flower and strobe
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109875 EUROLITE LED KLS-1001 Compact lightset, 51918557 EUROLITE LED MAT-Bar Hybrid matrix bar, 2 x 42109925 EUROLITE LED ACS BAR-12 RGB 12x1W, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
 - KLS-1001 Compact lightset
 - Complete LED light set with 4 spots
 - Compact and easy to transport
 - 48 TCL LEDs
 - 4 IEC outputs for power supply of further devices
 - LED MAT-Bar Hybrid matrix bar
 - The colorful flower-beams change their direction of movement at every bass-beat in sound controlled mode
 - Functions: static colors, internal programs, strobe effect, Master/Slave
 - Convenient controlling possible via easy-to-handle remote control
 - Equipped with 256 x 5mm RGBAW LEDs as well as 108 x SMD LEDs in white
 - ACS BAR-12 12x1W
 - Equipped with 12 x 1 W LEDs
 - Beam angle approximately 16°
 - Floor, ceiling or trussing installation possible
 - LED intensity and strobe settings
- You can find more information under the respective article

Logistic

EUROLITE LED KLS-1001 Compact-Light-Set

DMX LED spotlight set with 48 x 3in1 LED for mobile use

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 12 TCL LEDs per spot
- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- DMX512 control via regular DMX controller (occupies 15 channels)
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- Control via stand-alone; DMX; Foot switch (optional); IR remote control (optional)
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNITRONIC Speaker System Stand alu bk

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Package contents

- 1 x device, 1 x user manual, 2 x knurled screw

EUROLITE LED MAT-Bar Hybrid Matrix Bar

Combination of Mat-Bar and strobe

- Hybrid effect - LED flower and strobe in one device
- Equipped with 256 x 5mm LEDs (RGBAW) as well as 108 x SMD LEDs in white
- Functions: static colors, internal programs, strobe effect, Master/Slave
- Addressing and setting via control panel with 4-digit LED screen and three operating buttons
- Convenient control via easy-to-handle remote control (accessory)
- Control also via Wi-Fi networks with your tablet or smartphone and the Eurolite Hybrid App plus the USB-DMX interface (item 51860120) and the light control software FreeStyler (freeware)
- Eurolite Hybrid App is available for free in the App Store
- Operable in stand-alone mode or with DMX512 interface
- DMX-512 control via regular DMX-controller (occupies max. 10 channels)
- 2 or 10 DMX channels selectable for numerous applications

- Sound controlled via built-in microphone
- Microphone-sensitivity adjustable via rotary-control
- The colorful flower-beams change their direction of movement at every bass-beat in sound controlled mode
- Rugged compact housing
- Ready for connection via IEC power cord with safety-plug
- Including mounting bracket and mounting hole with fixation screw for installation on a trussing system or speaker stand
- Carrying bag included in delivery
- Switch-mode power supply allows for automatic power supply adaption between 100 and 240 Volts without power selector
- Preprogrammed in Light´J

EUROLITE LED ACS BAR-12 RGB 12x1W

Handy professional light bar with RGB color mixture

- Operable in stand-alone mode or via DMX
- 3 or 5 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via control panel
- Comfortable addressing and setting via control panel with LED screen and three operating buttons
- Functions: Static colors, RGB color mixture, 6 internal programs, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 12 x 1 W LEDs
- Beam angle approximately 16°
- Floor, ceiling or trussing installation possible
- Locking possibility at the mounting bracket
- Ready for connection via power cord with IEC plug for direct KLS-connection
- For stand alone operation you need a normal power cord with safety plug
- 12 powerful LEDs 1 W high-power R/G/B (homogenous color mix)
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512
- With a beam angle of 16°

OMNITRONIC XLR cable 3pin 0.5m bk

Audio cable with 3-pin XLR connectors<p class='attributgroup'>Package contents

- 1 x xLR cable

Technical specifications:

Weight:	27,12 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED KLS-1001 Compact-Light-Set

Power supply:	230 V AC, 50 Hz
Power consumption:	180,00 W
IP classification:	IP20
Lamp type:	LED lamp
Control:	Stand-alone; DMX; Foot switch (optional); IR remote control (optional)

Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle (1/2 peak):	18°
Housing color:	Black
Dimensions:	Width: 1,2 m Depth: 6,5 cm Height: 31,5 cm
Weight:	12,65 kg
DMX channels:	15
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	3 W TCL
Number of LEDs:	48
Beam angle:	18°
TV spigot:	D = 28 mm
Dimensions (L x W x H):	1200 x 65 x 315 mm
Dimensions case (L x W x H):	1250 x 120 x 380 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3,45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Max. load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8,50 cm Depth: 5 cm Height: 19,50 cm

Weight: 1,50 kg

EUROLITE LED MAT-Bar Hybrid Matrix Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	17,00 W
Preprogrammed in:	Light J
Dimensions:	Width: 80 cm Depth: 22,5 cm Height: 85,5 cm
Weight:	6,40 kg
DMX channels:	2/10
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5mm-RGBAW / SMD-white
LED number:	256 / 108
Beam angle:	15°
Mounting hole:	D = 36 mm
Dimensions (L x W x H):	800 x 223.5 x 85.5 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED ACS BAR-12 RGB 12x1W

Power supply:	230 V AC, 50 Hz
Power consumption:	20,00 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED:	12 x 1 W high-power R/G/B (homogenous color mix)
DMX channels:	3; 5
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	Light J; LED PC-Control 512
Beam angle:	16°
Beam angle (1/2 peak):	16°
Housing color:	Black
Dimensions:	Width: 28,5 cm Depth: 8 cm Height: 13 cm
Weight:	1,48 kg
DMX connection:	3-pin XLR
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting

OMNITRONIC XLR cable 3pin 0.5m bk

Cable construction:	Audio cable
Cable length:	0,5 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	80 g
