

EUROLITE LED KLS-60 WW Compact Light Set

Bar with 4 bright, warm white spots, QuickDMX port, IR remote control and bag

Art. No.: 42109602

GTIN: 4026397675818



List price: 403.41 €

incl. 19% VAT.

Features:

- Compact lightweight
 - Spots can be turned 170° vertically and 340° horizontally
 - 4 powerful LEDs 15 W high-power warm white (WW)
4 spots controlled separately
 - 12 integrated show programs
 - Silent operation
 - Strobe effect
 - Dimmer electronic
 - Very high color rendering index (CRI)
 - Flicker-free
 - Multicolor OLED display
 - Control via DMX; stand-alone; IR remote control; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in Light Captain
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Mobile use; Wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x device, 1 x user manual, 1 x power cord, 8 x diffusor cover, 1 x remote control, 1 x bag, 1 x omega bracket

Logistic

EAN / GTIN: 4026397675818

Weight: 4,65 kg

Length: 0.57 m

Width: 0.13 m

Height: 0.31 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	4 x 15 W high-power warm white (WW)
Color temperature:	3200K
DMX channels:	1; 3; 4; 5; 7; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	5°
Beam angle (1/2 peak):	5° 11° 24°
Beam angle (1/10 peak):	10° 24° 43°
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Warm white (WW) 1m: 16000 lx, 3m: 1200 lx, 6m: 350 lx
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Display type:	Multicolor OLED display
Dimensions:	Width: 51 cm Depth: 12,1 cm Height: 21,2 cm
Weight:	4,20 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting