

## EUROLITE LED KLS-120 FX Compact Light Set

DMX lighting effect bar with 2 rotating LED derbies and 2 LED spotlights

Art. No.: 42109607

GTIN: 4026397680751



### Features:

- Crossbar with integrated DMX control unit and stand sleeve
  - Compact lightweight
  - 2 rotating derbies for mirror ball effects
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect
  - 3 integrated show programs
  - Direct color selection for 15 preset colors
  - The device is cooled by passive convection cooling
  - Control via DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Fixtures available for Light Captain; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
  - Flicker-free
  - With a beam angle of 18°
  - 4 digit 7-segment LED display
  - 6 x rubber feet
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
  - Silent operation
  - Application possibility: Standing; on stand
- spotlight**
- 3 LEDs 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)<BR> spots controlled separately
- light effect**
- 4 LEDs 3 W SMD 9080 R/G/B/W<BR> LEDs controlled separately

### Logistic

EAN / GTIN: 4026397680751

Weight: 5,40 kg

Length: 0.66 m

Width: 0.17 m

Heigh: 0.36 m

## Technical specifications:

|                         |                                                                                                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                                                       |
| Power consumption:      | 45 W                                                                                                                                                                                                         |
| IP classification:      | IP20                                                                                                                                                                                                         |
| Protection class:       | Protection class I                                                                                                                                                                                           |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug included                                                                                                               |
| Power output:           | IEC connector (F) mounting version                                                                                                                                                                           |
| Fuse:                   | T 1 A fuse replaceable                                                                                                                                                                                       |
| Lamp type:              | LED lamp                                                                                                                                                                                                     |
| Flash rate:             | 0.5 - 20 Hz                                                                                                                                                                                                  |
| DMX channels:           | 2; 9; 21                                                                                                                                                                                                     |
| DMX input:              | 3-pin XLR (F) mounting version                                                                                                                                                                               |
| DMX output:             | 3-pin XLR (M) mounting version                                                                                                                                                                               |
| Cooling:                | Passive convection cooling                                                                                                                                                                                   |
| Control:                | DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief                                                                                                                                                 |
| Projection:             | Flicker-free                                                                                                                                                                                                 |
| PWM frequency:          | 2900 Hz                                                                                                                                                                                                      |
| Beam angle:             | 18°                                                                                                                                                                                                          |
| Beam angle (1/2 peak):  | Wash effect 18°<br>Multi beam effect 90° multicolor                                                                                                                                                          |
| Housing color:          | Black                                                                                                                                                                                                        |
| Attachment system:      | Tube: 1x Ø 35mm                                                                                                                                                                                              |
| Display type:           | 4 digit 7-segment LED display                                                                                                                                                                                |
| Transport aid:          | 6 x rubber feet                                                                                                                                                                                              |
| Dimensions:             | Width: 62.5 cm<br>Depth: 15.5 cm<br>Height: 22.4 cm                                                                                                                                                          |
| Weight:                 | 4.70 kg                                                                                                                                                                                                      |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                                                                                    |
| LED type:               | 4 x 3 W SMD 9080 R/G/B/W                                                                                                                                                                                     |
| Cable construction:     | H05VV-F                                                                                                                                                                                                      |
| Cable length:           | Approx. 1.2 m                                                                                                                                                                                                |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                                                                                                                      |
| LED type:               | 3 x 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)                                                                                                                                             |
| Special product:        | Not designed for household room illumination                                                                                                                                                                 |
| Intended use:           | Show effect lighting                                                                                                                                                                                         |

## Scope of delivery:

---

1 x light effect  
1 x power cord  
1 x remote control  
1 x battery  
1 x bag  
1 x user manual