

## EUROLITE LED KLS-190 Compact Light Set

Bar with 4 RGB spots, 4 white strobe LEDs and QuickDMX USB port

Art. No.: 42109608

GTIN: 4026397657715



### Features:

- Crossbar with integrated DMX control unit and stand sleeve
  - Compact lightweight
  - Two additional frost filters provide a soft, homogeneous light
  - Movable and tiltable spotlights
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect
  - 19 integrated show programs
  - Direct color selection for 18 preset colors
  - The device is cooled by passive convection cooling
  - Control via DMX; sound to light via microphone; IR remote control; master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Fixtures available for EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
  - With a beam angle of 9°
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
  - Silent operation
  - Application possibility: On stand; suspended
- spotlight**
- 4 LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)<BR> spots controlled separately
- bar**
- 4 LEDs 3 W high-power cold white (CW)<BR> LEDs controlled separately

### Logistic

EAN / GTIN: 4026397657715

Weight: 7,80 kg

Length: 0.72 m

Width: 0.23 m

Height: 0.35 m

## Technical specifications:

---

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Lamp type:	LED lamp
DMX channels:	4; 6; 7; 9; 13; 16
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; IR remote control; master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; Light J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle:	9°
Beam angle (1/2 peak):	9° 42°
Beam angle (1/10 peak):	20° 72°
Housing color:	Black
Dimensions:	Width: 66.0 cm Depth: 15.0 cm Height: 26.5 cm
Weight:	6.29 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
LED type:	4 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
LED type:	4 x 3 W high-power cold white (CW)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

---

1 x spotlight  
1 x user manual  
1 x power cord  
1 x remote control  
1 x battery  
1 x bag  
8 x frost filter