

EUROLITE LED KLS-180 Compact Light Set

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

Art. No.: 42109630

GTIN: 4026397599046



List price: 308.21 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Silent operation
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Strobe effect
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
- Flicker-free
- Preprogrammed in EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
- With Mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
- Application possibility: On stand

spotlight

- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
 4 spots controlled separately

bar

- 4 powerful LEDs 1 W high-power cold white (CW)
 LEDs controlled separately

Package contents

- 1 x spotlight, 1 x bag, 1 x remote control, 1 x battery, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397599046

Weight: 5,50 kg

Length: 0.66 m

Width: 0.19 m

Height: 0.29 m

Technical specifications:

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 80 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Cable length: | Approx. 1,1 m |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| DMX channels: | 3; 4; 8; 21 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional) |
| Preprogrammed in: | EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J |
| Projection: | Flicker-free |
| Beam angle: | 9° |
| Beam angle (1/2 peak): | 9° |
| Beam angle (1/10 peak): | 18° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | Monochrome 4 digit 7-segment LED display |
| Dimensions: | Width: 60,5 cm Depth: 14 cm Height: 23 cm |
| Weight: | 4,85 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Spotlight | |
| LED: | 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Bar | |
| LED: | 4 x 1 W high-power cold white (CW) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |