

## EUROLITE LED KLS-180/6 Compact Light Set

Bar with 6 RGBW spots and 6 white strobe LEDs

Art. No.: 42109632

GTIN: 4026397690408



List price: 474.81 €

incl. 19% VAT.

### Features:

- Crossbar with integrated DMX control unit and stand sleeve
  - Movable and tiltable spotlights
  - Control via IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Flicker-free
  - With a beam angle of 9°
  - Dimmer electronic; color blend stepless; color change adjustable; colors preset
  - Strobe effect
  - Preprogrammed in EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
  - For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
  - Silent operation
  - Application possibility: Suspended; on stand
- spotlight**
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix) <BR> 6 spots controlled separately
- bar**
- 6 powerful LEDs 1 W high-power cold white (CW) <BR> LEDs controlled separately
- Package contents**
- 1 x device, 1 x bag, 1 x remote control, 1 x battery, 1 x power cord, 1 x user manual

### Logistic

EAN / GTIN: 4026397690408  
Weight: 7,60 kg  
Length: 0.96 m  
Width: 0.20 m  
Height: 0.30 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	90 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	2 x IEC connector (F) mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
DMX channels:	3; 4; 6; 8; 9; 11; 21; 24; 29
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
Projection:	Flicker-free
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 92,6 cm Depth: 14,6 cm Height: 26,7 cm
Weight:	6,00 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Spotlight	
LED:	4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Bar	
LED:	6 x 1 W high-power cold white (CW)
Flash rate:	0 - 20 Hz
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting