

EUROLITE LED KLS-902 Next Compact Light Set

Bar with 4 powerful 4in1 QCL RGB/WW spots, QuickDMX support, IR remote control and carrying bag

Art. No.: 42109860

GTIN: 4026397673166



The article is no longer in our assortment.

Features:

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
 - Mounting points and power outlets for additional fixtures
 - 5 powerful LEDs 7 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
 spots controlled separately
 - Color blend stepless; Dimmer electronic; program selection
 - 20 integrated show programs
 - The device is cooled by passive convection cooling
 - Control via DMX; stand-alone; sound to light via microphone; IR remote control; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light'J; EASY SHOW 3; Colorchief
 - With a beam angle of 16°
 - TV spigot
 - With omega bracket
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Mobile use; stage; mobile djs / entertainer; small rental; rental
 - Very quiet working noise
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x omega bracket, 1 x declaration of conformity, 4 x knurled screw, 1 x bag

Logistic

EAN / GTIN: 4026397673166

Weight: 10,80 kg

Length: 1.13 m

Width: 0.38 m

Heigh: 0.18 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version 1 x P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 2 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A fuse replaceable
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED type:	5 x 7 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 16; 20; 18
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; IR remote control; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light´J; EASY SHOW 3; Colorchief
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Dimensions:	Width: 108 cm Depth: 6 cm Height: 28 cm
Weight:	9,80 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting