

EUROLITE LED Pixel Tower

Multifunctional vertical light effect with mounting option on the supplied case

Art. No.: 42109900

GTIN: 4026397657128



List price: 1188.81 €

incl. 19% VAT.

Features:

- Every LED bar can be manually rotated centrally at the joint
- Connection between the two LED bars can be extended spatially at will via P-Con and 3-pin XLR cables
- 80 powerful LEDs 0,3 W SMD 5050 warm white (WW)
4 segments controlled separately
- 20 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Strobe effect
- 96 integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; stand-alone
- With a beam angle of 8°
- TV spigot
- Silent operation
- Preprogrammed in LED PC-Control 512; Light Captain; Light´J
- With Mounting bracket
- For application areas such as: Wedding/gala/events; mobile use; Stage; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 2 x segment, 1 x remote control, 1 x case, 1 x user manual, 2 x power cord, 4 x angle, 1 x stand, 4 x washer, 4 x diffusor cover, 8 x knurled screw, 1 x holder, 2 x mounting bracket, 3 x xLR cable

Logistic

EAN / GTIN: 4026397657128

Weight: 28,30 kg

Length: 1.10 m

Width: 0.42 m

Height: 0.17 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	250 W
IP classification:	IP20
Lamp type:	LED lamp
LED:	80 x 0,3 W SMD 5050 warm white (WW) 20 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	12; 20; 27; 84; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; stand-alone
Preprogrammed in:	LED PC-Control 512; Light Captain; Light´J
Beam angle:	8°
Beam angle (1/2 peak):	8°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Mounting bracket
Weight:	12,00 kg
Noise classification:	Class 0 (no noise at all)
Device	
Dimensions:	Length: 1,1 m Width: 44 cm Height: 2 m
Segment	
Dimensions:	Length: 92 cm Width: 10,1 cm Height: 7 cm
Case	
Dimensions:	Length: 1,1 m Width: 44 cm Height: 18 cm
Remote control	
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in