

EUROLITE LED PARty Hybrid Spot

LED effect spotlight with RGB LEDs and stroboscope


Art. No.: 42110198 GTIN: 4026397651911











incl. 19% VAT.

Features:

- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- 18 powerful LEDs 0,5 W SMD 5730 cold white (CW)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 3 integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; stand-alone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain; Colorchief
- With a beam angle of 22°
- With double bracket
- 4 digit 7-segment LED display
- For application areas such as: Party room; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

· 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	16 W
IP classification:	IP20
Protection class:	Protection class II

Logistic

EAN / GTIN: 4026397651911

Weight: 0,61 kg Length: 0.17 m Width: 0.16 m Heigth: 0.13 m

LED type: LED type: 3 x 3 W high-power 3in1 TCL RGB (homogenous color mix) 18 x 0,5 W SMD 5730 cold white (CW) DMX channels: 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: DMX; sound to light via microphone; stand-alone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; Colorchief Beam angle: 22° Beam angle (1/10 peak): 37° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
color mix) 18 x 0,5 W SMD 5730 cold white (CW) DMX channels: 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: DMX; sound to light via microphone; stand-alone Preprogrammed in: Light J; LED PC-Control 512; Light Captain; Colorchief Beam angle: 22° Beam angle (1/2 peak): 22° Beam angle (1/10 peak): 37° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
DMX channels: 7 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: DMX; sound to light via microphone; stand-alone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; Colorchief Beam angle: 22° Beam angle (1/2 peak): 22° Beam angle (1/10 peak): 37° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: DMX; sound to light via microphone; stand-alone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; Colorchief Beam angle: 22° Beam angle (1/2 peak): 22° Beam angle (1/10 peak): 37° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Passive convection cooling Control: DMX; sound to light via microphone; stand-alone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; Colorchief Beam angle: 22° Beam angle (1/2 peak): 22° Beam angle (1/10 peak): 37° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Cooling: Passive convection cooling Control: DMX; sound to light via microphone; stand-alone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; Colorchief Beam angle: 22° Beam angle (1/2 peak): 22° Beam angle (1/10 peak): 37° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Control: DMX; sound to light via microphone; stand-alone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; Colorchief Beam angle: 22° Beam angle (1/2 peak): 22° Beam angle (1/10 peak): 37° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; Colorchief Beam angle: 22° Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Colorchief Beam angle: 22° Beam angle (1/2 peak): 22° Beam angle (1/10 peak): 37° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Beam angle (1/10 peak): Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Housing color: Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Attachment system: Double bracket 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Material: Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Dimensions: Width: 15,2 cm Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Depth: 12 cm Height: 17 cm Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Weight: 0,52 kg Noise classification: Class 0 (no noise at all)
Noise classification: Class 0 (no noise at all)
Mounting bracket
Diameter mounting holes: 1 x Ø10mm
Material: Metal, 1 mm
Power cord
Cable construction: 2 x 0,75 mm² H03VVH2-F
Cable length: Approx. 0,9 m
Legal specifications
Special product: Not designed for household room illumination
Intended use: Show effect lighting