

EUROLITE LED Outdoor Spot 15W RGBW QuickDMX with stake

Weather-proof LED spotlight (IP65) with 15 W LED, incl. IR remote control, frost filter & ground stake

Art. No.: 50498638

GTIN: 4026397696301



List price: 224.91 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- 1 powerful LED 15 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; QuickDMX; Master/slave function; stand-alone; Sound to light via Microphone; DMX
- 3 buttons on the remote control for saving your own settings
- Flicker-free
- Easy installation
- With a beam angle of 9°
- With Mounting bracket
- LCD display
- Suitable for outdoor use IP65
- Preprogrammed in Light Captain; Light´J
- With pressure compensation membrane
- Silent operation
- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; standing; on stand

Package contents

Logistic

EAN / GTIN: 4026397696301

Weight: 1,80 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.15 m

- 1 x light effect, 1 x stake, 1 x remote control, 1 x diffusor cover, 1 x screw, 2 x washer, 1 x declaration of conformity, 1 x user manual

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 16 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable length: | Approx. 1 m |
| Lamp type: | LED lamp |
| LED: | 1 x 15 W 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 1 - 23 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| Cooling: | Passive convection cooling |
| Control: | IR remote control; QuickDMX; Master/slave function; stand-alone; Sound to light via Microphone; DMX |
| Preprogrammed in: | Light Captain; Light´J |
| Projection: | Flicker-free |
| Carrier frequency: | 2,4 GHz |
| Setup: | Easy installation |
| Beam angle: | 9° |
| Beam angle (1/2 peak): | 9° |
| Beam angle (1/10 peak): | 22° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Material: | Aluminum casting |
| Dimensions: | Length: 14,3 cm Width: 11,0 cm Depth: 18,4 cm |
| Weight: | 1,52 kg |
| Noise classification: | Class 0 (no noise at all) |
| Mounting bracket | |
| Diameter mounting holes: | 3 x Ø11mm; 2 x Ø6,5mm |
| Material: | Aluminum, 2 mm |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |