# eurolite®

### **EUROLITE LED Neon Flex 24V 5m WW Set**

Flexible light tube with 600 x warm white (WW) LEDs, power supply units & remote control, IP44, 2100 Im GTIN: 4026397705157



Art. No.: 50499901



## List price: 53.43 €

incl. 19% VAT.

#### Features:

- Extremely flexible light tube with silicone coating
- LED Neon Flex creates the effect of conventional neon light
- Continuously bright, uniform light without visible dots
- Ready-to-use set including power adapter, supply cable and mounting clips
- Not shortenable or extendable
- Dimmable
- 600 powerful LEDs warm white (WW)
- Control via plug and play
- Easy installation
- Good color rendering index (CRI)
- Suitable for outdoor use IP44
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; installation; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting
- Package contents
- 1 x illuminant, 1 x external mains adapter, 10 x fixation clip, 1 x screw, 1 x user manual

#### Technical specifications:

Power supply:	24V DC
Power consumption:	21 W
IP classification:	IP44

#### Logistic

EAN / GTIN: 4026397705157 Weight: 0,93 kg Length: 0.18 m Width: 0.18 m Heigth: 0.07 m

Power connection:Mains input via 2-pin screw plug connector (M) IPCable length:Approx. 1.6 mLamp specification:DimmableLED type:600 x warm white (WW)Light emission:Top 9 mm Bottom 1.5 mmControl:Plug and playSetup:Easy installationColor of light:Warm white WW <3300 KColor of light:Warm white WW <3300 KColor of light:Warm white WW <3300 KColor rendering index (CRI):82 RaLamps/meter:12 pc/pcsPower/meter:4.2 WLamps/lube:600 pc/pcsLamps/lube:600 pc/pcsLamps/lube:2000 hLuminous flux:2100 lmLuminous flux:100 lmLuminous flux:100 lmLuminous flux:100 lmLuminous flux:100 lmLuminous flux:200 lm/mHousing color:Semi-transparentDimensions:Length: 500 cmWidth: 1 cm Height: 1.6 cmWeight:0.85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:Power supply:230 V AC, 50 HzIP classification:Pl44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipIsaDiameter mounting holes:1 x Ø3mmMaterial:Plastic	Protection class:	Protection class III
Lamp specification:DimmableLED type:600 x warm white (WW)Light emission:Top 9 mm Bottom 1,5 mmControl:Plug and playSetup:Easy installationColor of light:Warm white WW <3300 K	Power connection:	Mains input via 2-pin screw plug connector (M) IP
LED type:600 x warm white (WW)Light emission:Top 9 mm Bottom 1,5 mmControl:Plug and playSetup:Easy installationColor of light:Warm white WW <3300 K	Cable length:	Approx. 1,6 m
Light emission:Top 9 mm Bottom 1,5 mmControl:Plug and playSetup:Easy installationColor of light:Warm white WW <3300 K	Lamp specification:	Dimmable
Bottom 1,5 mmControl:Plug and playSetup:Easy installationColor of light:Warm white WW <3300 K	LED type:	600 x warm white (WW)
Setup:Easy installationColor of light:Warm white WW <3300 K	Light emission:	
Color of light:Warm white WW <3300 KColor temperature:2740KColor rendering index (CRI):82 RaLamps/meter:12 pc/pcsPower/meter:4,2 WLamps/tube:600 pc/pcsLamp s/tube:600 pc/pcsLamp s/tube:2100 lmLuminous flux:2100 lmLuminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cmWidth: 1 cmHeight: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterProtection class IIPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipDiameter mounting holes:1 x Ø3mmMaterial:PlasticPlastic	Control:	Plug and play
Color temperature:2740KColor rendering index (CRI):82 RaLamps/meter:12 pc/pcsPower/meter:4,2 WLamps/tube:600 pc/pcsLamps/tube:600 pc/pcsLamps/tube:2100 lmLuminous flux:2100 lmLuminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cm Width: 1 cm Height: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterProtection class:Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clip1 x Ø3mmMaterial:Plastic	Setup:	Easy installation
Color rendering index (CRI):82 RaLamps/meter:12 pc/pcsPower/meter:4,2 WLamps/tube:600 pc/pcsLamps/tube:600 pc/pcsLamps/tube:2100 lmLuminous flux:2100 lmLuminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:Power supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipDiameter mounting holes:1 x Ø3mmMaterial:PlasticPlastic	Color of light:	Warm white WW <3300 K
Lamps/meter:12 pc/pcsPower/meter:4,2 WLamps/tube:600 pc/pcsLamp life:30000 hLuminous flux:2100 lmLuminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cmWidth: 1 cmHeight: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:Power supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipDiameter mounting holes:1 x Ø3mmMaterial:PlasticPlastic	Color temperature:	2740K
Power/meter:4,2 WLamps/tube:600 pc/pcsLamp life:30000 hLuminous flux:2100 lmLuminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cm Width: 1 cm Height: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipI1 x Ø3mmMaterial:Plastic	Color rendering index (CRI):	82 Ra
Lamps/tube:600 pc/pcsLamps/tube:600 pc/pcsLamp life:30000 hLuminous flux:2100 lmLuminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cmWidth: 1 cmHeight: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:Power supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipIDiameter mounting holes:1 x Ø3mmMaterial:Plastic	Lamps/meter:	12 pc/pcs
Lamp life:30000 hLuminous flux:2100 lmLuminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cm Width: 1 cm Height: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipIn x Ø3mmDiameter mounting holes:1 x Ø3mmMaterial:Plastic	Power/meter:	4,2 W
Luminous flux:2100 lmLuminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cm Width: 1 cm Height: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipI x Ø3mmMaterial:Plastic	Lamps/tube:	600 pc/pcs
Luminous flux (Lumen) per meter:420 lm/mHousing color:Semi-transparentDimensions:Length: 500 cm Width: 1 cm Height: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipI x Ø3mmMaterial:Plastic	Lamp life:	30000 h
Housing color:Semi-transparentDimensions:Length: 500 cm Width: 1 cm Height: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipI x Ø3mmMaterial:Plastic	Luminous flux:	2100 lm
Dimensions:Length: 500 cm Width: 1 cm Height: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipI x Ø3mmDiameter mounting holes:1 x Ø3mmMaterial:Plastic	Luminous flux (Lumen) per meter:	420 lm/m
Width: 1 cm Height: 1,6 cmWeight:0,85 kgNoise classification:Class 0 (no noise at all)External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clip1 x Ø3mmMaterial:Plastic	Housing color:	Semi-transparent
Noise classification:Class 0 (no noise at all)External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipI x Ø3mmMaterial:Plastic	Dimensions:	Width: 1 cm
External mains adapterPower supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipImage: Streme terminalDiameter mounting holes:1 x Ø3mmMaterial:Plastic	Weight:	0,85 kg
Power supply:230 V AC, 50 HzIP classification:IP44Protection class:Protection class IIConnections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipIDiameter mounting holes:1 x Ø3mmMaterial:Plastic	Noise classification:	Class 0 (no noise at all)
IP classification:       IP44         Protection class:       Protection class II         Connections:       Output: screw plug-in terminal         Output:       24 V DC; 1 A; 24 W         Color:       Black         Weight:       0,1 kg         Fixation clip       Diameter mounting holes:         1 x Ø3mm       Material:	External mains adapter	
Protection class:     Protection class II       Connections:     Output: screw plug-in terminal       Output:     24 V DC; 1 A; 24 W       Color:     Black       Weight:     0,1 kg       Fixation clip	Power supply:	230 V AC, 50 Hz
Connections:Output: screw plug-in terminalOutput:24 V DC; 1 A; 24 WColor:BlackWeight:0,1 kgFixation clipDiameter mounting holes:Diameter mounting holes:1 x Ø3mmMaterial:Plastic	IP classification:	IP44
Output:     24 V DC; 1 A; 24 W       Color:     Black       Weight:     0,1 kg       Fixation clip     Diameter mounting holes:       Diameter mounting holes:     1 x Ø3mm       Material:     Plastic	Protection class:	Protection class II
Color:     Black       Weight:     0,1 kg       Fixation clip	Connections:	Output: screw plug-in terminal
Weight:     0,1 kg       Fixation clip       Diameter mounting holes:     1 x Ø3mm       Material:     Plastic	Output:	24 V DC; 1 A; 24 W
Fixation clip       Diameter mounting holes:       1 x Ø3mm       Material:   Plastic	Color:	Black
Diameter mounting holes:     1 x Ø3mm       Material:     Plastic	Weight:	0,1 kg
Material: Plastic	Fixation clip	
	Diameter mounting holes:	1 x Ø3mm
Color: Semi-transparent	Material:	Plastic
	Color:	Semi-transparent