


EUROLITE LED Neon Flex 24V 5m WW Set

Art. No.: 50499901

Flexible light tube with 600 x warm white (WW) LEDs, power supply units & remote control, IP44, 2100 lm GTIN: 4026397705157



List price: 53.43 €

incl. 19% VAT.

Features:

- Extremely flexible light tube with silicone coating
- LED Neon Flex creates the effect of conventional neon light
- Continuously bright, uniform light without visible dots
- Ready-to-use set including power adapter, supply cable and mounting clips
- Not shortenable or extendable
- Dimmable
- 600 powerful LEDs warm white (WW)
- Control via plug and play
- Easy installation
- Good color rendering index (CRI)
- Suitable for outdoor use IP44
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; Installation; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting

Logistic

EAN / GTIN: 4026397705157

Weight: 0,93 kg

Length: 0.18 m

Width: 0.18 m

Height: 0.07 m

Package contents

- 1 x illuminant, 1 x external mains adapter, 10 x fixation clip, 1 x screw, 1 x user manual

Technical specifications:

Power supply: 24 V DC

Power consumption: 21 W

IP classification: IP44

Protection class:	Protection class III
Power connection:	Mains input via 2-pin screw plug connector (M) IP
Cable length:	Approx. 1,6 m
Lamp specification:	Dimmable
LED:	600 x warm white (WW)
Color of light:	Warm white WW <3300 K
Color temperature:	2740K
Light emission:	Top 9 mm Bottom 1,5 mm
Control:	Plug and play
Setup:	Easy installation
Color rendering index (CRI):	82 Ra
Lamps/meter:	12 pc/pcs
Power/meter:	4,2 W
Lamps/tube:	600 pc/pcs
Lamp life:	30000 h
Luminous flux:	2100 lm
Luminous flux (Lumen) per meter:	420 lm/m
Housing color:	Semi-transparent; Frost
Dimensions:	Length: 5 m Width: 1 cm Height: 1,6 cm
Weight:	850 g
Noise classification:	Class 0 (no noise at all)
Fixation clip	
Diameter mounting holes:	1 x Ø3mm
Material:	Plastic
Color:	Semi-transparent
External mains adapter	
Power supply:	230 V AC, 50 Hz
IP classification:	IP44
Protection class:	Protection class II
Connections:	Output: screw plug-in terminal
Output:	24 V DC; 1 A; 24 W
Color:	Black
Weight:	100 g