

EUROLITE FIB-450 LED Fiber Light RGB DMX

Fiber light with RGB color change and DMX control

Art. No.: 50520260

GTIN: 4026397388510



List price: 236.81 €

incl. 19% VAT.

Features:

- Fibre optic strands are bundled together and attached onto an illuminator
- Light is transmitted along the length of the fibres to shine at the tips
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- 1 powerful LED 9 W high-power 3in1 TCL RGB
- Color selection manual; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in LED PC-Control 512
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels
- Silent operation

Package contents

- 1 x device, 1 x external mains adapter, 450 x fibre optic strand length, 1 x XLR cable, 1 x user manual

Logistic

EAN / GTIN: 4026397388510

Weight: 1,10 kg

Length: 0.25 m

Width: 0.29 m

Height: 0.05 m

Technical specifications:

Power supply:	5V DC
---------------	-------

Power consumption:	12 W
--------------------	------

IP classification:	IP20
--------------------	------

Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
LED type:	1 x 9 W high-power 3in1 TCL RGB
DMX channels:	4
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512
Connector type:	3-pin XLR (F); 3-pin XLR (F)
Fibre optic strand length:	450 pc/pcs
Housing color:	Silvergrey
Diameter mounting holes:	4 x Ø4mm
Material:	Metal, 1 mm
Weight:	0,99 kg
Noise classification:	Class 0 (no noise at all); class 2 (slight noise)
Photobiological safety:	Risk Group 0
Device	
Dimensions:	Width: 19,5 cm Depth: 8,5 cm Height: 5 cm
External mains adapter	
Power supply:	100-240 V AC, 50/60 Hz
Pin configuration:	Inside + / outside -
Cable length:	Approx. 1,5 m
Output:	5 V DC; 2,5 A;
Color:	Black
Fibre optic strand length	
Dimensions:	Length: 200 cm Diameter: Ø 0,075 cm
XLR cable	
Cable length:	Approx. 1,2 m
Connector type:	3-pin XLR (F); 3-pin XLR (M)
Color:	Black
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting