

# **EUROLITE FIB-450 LED Fiber Light RGB DMX**

Fiber light with RGB color change and DMX control

Art. No.: 50520260 GTIN: 4026397388510



List price: 236.81 €

incl. 19% VAT.

## Features:

- Fibre optic strands are bundled together and attached onto an illuminator
- Light is transmitted along the length of the fibres to shine at the tips
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- 1 powerful LED 9 W high-power 3in1 TCL RGB
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone
- Color selection manual; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Preprogrammed in LED PC-Control 512
- For application areas such as: Clubs/dancing school; Party room; restaurants, bars and hotels
- Silent operation

#### Package contents

 1 x device, 1 x external mains adapter, 450 x fibre optic strand length, 1 x xLR cable, 1 x user manual

### **Technical specifications:**

Power supply:	5 V DC
Power consumption:	12 W
IP classification:	IP20

## Logistic

EAN / GTIN: 4026397388510

Weight: 1,10 kg Length: 0.25 m Width: 0.29 m Heigth: 0.05 m

Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
LED:	1 x 9 W high-power 3in1 TCL RGB
DMX channels:	4
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512
Connector type:	3-pin XLR (F); 3-pin XLR (F)
Fibre optic strand length:	450 pc/pcs
Housing color:	Silvergrey
Diameter mounting holes:	4 x Ø4mm
Material:	Metal, 1 mm
Weight:	990 g
Noise classification:	Class 0 (no noise at all); class 2 (slight noise)
Photobiological safety:	Risk Group 0
Device	
Dimensions:	Width: 19,5 cm
	Depth: 8,5 cm
VI D coble	Height: 5 cm
XLR cable  Coble length:	Approx 12 m
Cable length:	Approx. 1,2 m
Connector type:	3-pin XLR (F); 3-pin XLR (M)
Color:	Black
External mains adapter	400 040 V AC FO/CO U-
Power supply:	100-240 V AC, 50/60 Hz
Pin configuration:	Inside + / outside -
Cable length:	Approx. 1,5 m
Output:	5 V DC; 2,5 A;
Color:	Black
Fibre optic strand length	Lagraphy Cas
Dimensions:	Length: 2 m Diameter: Ø 0,75 mm
Legal specifications	·
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting