

EUROLITE LED IP Strip 300 5m 3000K 12V

Flexible LED strip for indoor and outdoor use

Art. No.: 50530185 GTIN: 4026397426809





The article is no longer in our assortment.

Description:

With its numerous IP LED strips, Eurolite offers light on tape for outdoor use. Eurolite presents different stripes fulfilling the IP68 standard.

The flexible LED strips have a length of 5 meters. Unichrome versions - red, blue, green, yellow, cool white, warm white - are complimented by two RGB versions. The single colors can be ordered either with a wide span (150 LEDs) or with a short span (300 LEDs) between the LEDs. The RGB versions are available in 12 V or 24 operation - LED quantities are always 150. An optional LED controller controls the brightness and the speed of the RGB LEDs or provides automatic run of the built-in color programs.

Supplied on a plastic reel, the LED stripes feature a self adhesive rear side for simple installation. Color and form can be used as desired as the strips are very flexible and adaptable to really every venue.

Features:

- Flexible LED strip for decorative lighting
- Perfect for indirect lighting, custom-made versions for fair or shop applications as well as all kinds of background lighting
- For indoor and outdoor use (IP44)
- Can be cut into segments of variable size (groups of 3 LEDs)
- Self-adhesive rear side
- Supplied on a plastic reel
- Matching control units and power units optionally available
- Different versions available
- Suitable for outdoor use IP44

Logistic

EAN / GTIN: 4026397426809

Weight: 0,20 kg Length: 0.18 m Width: 0.18 m Heigth: 0.01 m

Technical specifications:

-	
Power consumption:	20 W
IP classification:	IP44
Standing/fixation:	Self adhesive
Lamps/meter:	60 pc/pcs
Power/meter:	4,8 W
Lamps/tube:	300 pc/pcs
Lamp distance:	16 mm
Cutting mark:	5 cm
Housing color:	White
Dimensions:	Length: 5 m
Weight:	180 g
Watts per meter/total:	4.8 W/max. 20 W
Protection grade:	IP44
LED type:	SMD 3528
LED number:	300
Color temperature:	3300 K
Cutting mark:	every 50 mm
Dimensions:	Ø 8 mm x 5000 mm