

# **EUROLITE Color-Changer-Set + PAR-36 Pinspot**

For starters

Art. No.: 50800530 GTIN: 4026397382242











### Features:

- Color-wheel with motor for T-36
- Spot and motor delivered with installed power cord and safety plug
- Use with alternative illuminants having differing beam angles (flood) is possible color wheel
- Color wheel with red, green, yellow, blue

## illuminant

- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

#### spotlight

- The device is cooled by passive convection cooling
- Control via plug and play
- With Mounting bracket

#### Motor for color wheel

- Control via plug and play

#### Package contents

1 x spotlight, 1 x illuminant, 1 x motor for color wheel, 2 x nut, 1 x color wheel, 1 x safety bond, 1 x chain link, 1 x lamp clamping ring, 1 x user manual

# **Technical specifications:**

Weight:	1,55 kg
Color wheel	
Color generation:	Color wheel with red, green, yellow, blue

# Logistic

EAN / GTIN: 4026397382242

Weight: 1,80 kg Length: 0.24 m Width: 0.14 m Heigth: 0.25 m

Material:         Plastic           Dimensions:         Width: 2 mm Diameter: Ø 23 cm           Illuminant         Dimenter: Ø 23 cm           Operating voltage:         6,4 V           Nominal wattage:         30 W           Base:         G-53 STC           Lamp type:         Halogen lamp; clear lamp           Lamp specification:         Dimmable Hot restrike           Color of light:         Warm white WW <3300 K           Beam angle (1/2 peak):         6°           Color rendering index (CRI):         99 Ra           Energy efficiency class (A - G):         G           Mounting bracket         Diameter mounting holes:           Diameter mounting holes:         3 x Ø10mm; 1 x Ø8mm           Material:         Metal, 2 mm           Spotlight         Power consumption:           Max. 30 W         Power convention:           IP classification:         IP20           Protection class:         Protection class I           Suitable lamp:         Max. 6,4 V/30 W PAR-36 G-53 STC           Power connection:         Fixed power supply cord with safety plug           Cable length:         Approx. 0,9 m           Base:         Wires           Cooling:         Passive convection cooling	Diameter mounting holes:	1 x Ø8mm
Diameter: Ø 23 cm	Material:	Plastic
Illuminant	Dimensions:	Width: 2 mm
Operating voltage:         6.4 V           Nominal wattage:         30 W           Base:         G-53 STC           Lamp type:         Halogen lamp; clear lamp           Lamp specification:         Dimmable Hot restrike           Color of light:         Warm white WW <3300 K		Diameter: Ø 23 cm
Nominal wattage:         30 W           Base:         G-53 STC           Lamp type:         Halogen lamp; clear lamp           Lamp specification:         Dimmable Hot restrike           Color of light:         Warm white WW <3300 K	Illuminant	
Base:         G-53 STC           Lamp type:         Halogen lamp; clear lamp           Lamp specification:         Dimmable Hot restrike           Color of light:         Warm white WW <3300 K	Operating voltage:	6,4 V
Lamp type: Halogen lamp; clear lamp  Lamp specification: Dimmable Hot restrike  Color of light: Warm white WW <3300 K  Beam angle (1/2 peak): 6°  Color rendering index (CRI): 99 Ra  Energy efficiency class (A - G): G  Mounting bracket  Diameter mounting holes: 3 x Ø10mm; 1 x Ø8mm  Material: Metal, 2 mm  Spotlight  Power supply: 230 V AC, 50 Hz  Power consumption: Max. 30 W  IP classification: IP20  Protection class: Protection class I  Suitable lamp: Max. 6, 4 V/30 W PAR-36 G-53 STC  Power connection: 5 x 0,75 mm² H05VV-F  Cable length: Approx. 0,9 m  Base: Wires  Cooling: Passive convection cooling  Control: Plug and play  Housing color: Black  Attachment system: Mounting bracket  Output: 6,44 AC;  Dimensions: Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power consumption: IP20  Protection class: Protection class I  Protection class: Protection coling Color whith safety plug  Cable construction: Plug and play  Housing color: Black  Attachment system: Mounting bracket  Output: 6,44 AC;  Dimensions: Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power supply: 230 V AC, 50 Hz  Power consumption: 4 W  IP classification: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: Fixed power supply cord with safety plug  Cable construction: Fixed power supply cord with safety plug  Cable construction: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F	Nominal wattage:	30 W
Lamp specification: Dimmable Hot restrike  Color of light: Warm white WW <3300 K  Beam angle (1/2 peak): 6° Color rendering index (CRI): 99 Ra  Energy efficiency class (A - G): Mounting bracket  Diameter mounting holes: 3 x Ø10mm; 1 x Ø8mm  Material: Metal, 2 mm  Spotlight  Power supply: 230 V AC, 50 Hz  Protection class: Protection class I  Suitable lamp: Max. 6,4 V/30 W PAR-36 G-53 STC  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 0,9 m  Base: Wires  Cooling: Passive convection cooling  Control: Housing color: Black Attachment system: Mounting bracket  Output: 6,4V AC; Dimensions: Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power consumption: Protection class I  Protection class I  Protection class I  Brack  Attachment system: Again and play  Housing color: Black  Attachment system: Attachment sy	Base:	G-53 STC
Color of light: Warm white WW <3300 K  Beam angle (1/2 peak): 6° Color rendering index (CRI): 99 Ra  Energy efficiency class (A - G): G  Mounting bracket  Diameter mounting holes: 3 x Ø10mm; 1 x Ø8mm  Material: Metal, 2 mm  Spotlight  Power supply: 230 V AC, 50 Hz  Power consumption: Max. 30 W  IP classification: IP20  Protection class: Protection class I  Suitable lamp: Max. 6, 4 V/30 W PAR-36 G-53 STC  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 0,9 m  Base: Wires  Cooling: Passive convection cooling  Control: Plug and play  Housing color: Black  Attachment system: Mounting bracket  Output: 6.4V AC;  Dimensions: Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power consumption: IP20  Protection class: Protection class I  Power consumption: IP20  Protection class: Protection class I  Power consumption: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: Fixed power supply cord with safety plug  Cable construction: Fixed power supply cord with safety plug	Lamp type:	Halogen lamp; clear lamp
Beam angle (1/2 peak):  Color rendering index (CRI):  Energy efficiency class (A - G):  G  Mounting bracket  Diameter mounting holes:  3 x Ø10mm; 1 x Ø8mm  Material:  Metal, 2 mm  Spotlight  Power supply:  230 V AC, 50 Hz  Power consumption:  Max. 30 W  IP classification:  IP20  Protection class:  Protection class I  Suitable lamp:  Max. 6,4 V/30 W PAR-36 G-53 STC  Power connection:  Cable length:  Approx. 0,9 m  Base:  Wires  Cooling:  Passive convection cooling  Control:  Plug and play  Housing color:  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power consumption:  4 W  IP classification:  IP20  Protection class I  Suitable Indiam in the system in the sy	Lamp specification:	
Second Color rendering index (CRI): 99 Ra	Color of light:	Warm white WW <3300 K
Energy efficiency class (A - G):  Mounting bracket  Diameter mounting holes:  3 x Ø10mm; 1 x Ø8mm  Material:  Metal, 2 mm  Spotlight  Power supply:  230 V AC, 50 Hz  Power consumption:  IP classification:  Protection class:  Protection class I  Suitable lamp:  Max. 6,4 V/30 W PAR-36 G-53 STC  Power connection:  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 0,9 m  Base:  Wires  Cooling:  Passive convection cooling  Control:  Plug and play  Housing color:  Black  Attachment system:  Mounting bracket  Output:  6,4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x Ø10mm; 1 x Ø8mm  Metal, 2 mm  Mex. 30 W  Ax. 30 W  Protection class I  Protection class:  Protection class:  Protection class:  Protection class:  Protection class:  Protection class:  Prover connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Beam angle (1/2 peak):	6°
Mounting bracket  Diameter mounting holes: 3 x Ø10mm; 1 x Ø8mm  Material: Metal, 2 mm  Spotlight  Power supply: 230 V AC, 50 Hz  Power consumption: Max, 30 W  IP classification: IP20  Protection class: Protection class I  Suitable lamp: Max, 6,4 V/30 W PAR-36 G-53 STC  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx, 0,9 m  Base: Wires  Cooling: Passive convection cooling  Control: Plug and play  Housing color: Black  Attachment system: Mounting bracket  Output: 6,4V AC;  Dimensions: Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power supply: 230 V AC, 50 Hz  Power consumption: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F	Color rendering index (CRI):	99 Ra
Diameter mounting holes:         3 x Ø10mm; 1 x Ø8mm           Material:         Metal, 2 mm           Spotlight         230 V AC, 50 Hz           Power consumption:         Max. 30 W           IP classification:         IP20           Protection class:         Protection class I           Suitable lamp:         Max. 6,4 V/30 W PAR-36 G-53 STC           Power connection:         Fixed power supply cord with safety plug           Cable construction:         3 x 0,75 mm² H05VV-F           Cable length:         Approx. 0,9 m           Base:         Wires           Cooling:         Passive convection cooling           Control:         Plug and play           Housing color:         Black           Attachment system:         Mounting bracket           Output:         6.4V AC;           Dimensions:         Length: 16 cm           Width: 15,5 cm         Height: 17 cm           Weight:         1 kg           Motor for color wheel         Power consumption:         4 W           IP classification:         IP20           Protection class:         Protection class I           Power connection:         Fixed power supply cord with safety plug           Cable construction:         3 x 0,75 mm²	Energy efficiency class (A - G):	G
Material:  Spotlight  Power supply:  230 V AC, 50 Hz  Power consumption:  Max. 30 W  IP classification:  IP20  Protection class:  Protection class I  Suitable lamp:  Max. 6,4 V/30 W PAR-36 G-53 STC  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 0,9 m  Base:  Wires  Cooling:  Passive convection cooling  Control:  Plug and play  Housing color:  Black  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Mounting bracket	
Spotlight  Power supply: 230 V AC, 50 Hz  Power consumption: Max. 30 W  IP classification: IP20  Protection class: Protection class I  Suitable lamp: Max. 6,4 V/30 W PAR-36 G-53 STC  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 0,9 m  Base: Wires  Cooling: Passive convection cooling  Control: Plug and play  Housing color: Black  Attachment system: Mounting bracket  Output: 6.4V AC;  Dimensions: Length: 16 cm  Width: 15,5 cm  Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power supply: 230 V AC, 50 Hz  Power consumption: 4 W  IP classification: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F	Diameter mounting holes:	3 x Ø10mm; 1 x Ø8mm
Power supply:         230 V AC, 50 Hz           Power consumption:         Max. 30 W           IP classification:         IP20           Protection class:         Protection class I           Suitable lamp:         Max. 6,4 V/30 W PAR-36 G-53 STC           Power connection:         Fixed power supply cord with safety plug           Cable construction:         3 x 0,75 mm² H05VV-F           Cable length:         Approx. 0,9 m           Base:         Wires           Cooling:         Passive convection cooling           Control:         Plug and play           Housing color:         Black           Attachment system:         Mounting bracket           Output:         6.4V AC;           Dimensions:         Length: 16 cm           Width: 15,5 cm         Height: 17 cm           Weight:         1 kg           Motor for color wheel           Power supply:         230 V AC, 50 Hz           Power consumption:         4 W           IP classification:         IP 20           Protection class:         Protection class I           Power connection:         Fixed power supply cord with safety plug           Cable construction:         3 x 0,75 mm² H05VV-F	Material:	Metal, 2 mm
Power consumption:    Max. 30 W     P classification:   IP20     Protection class:   Protection class I     Suitable lamp:   Max. 6,4 V/30 W PAR-36 G-53 STC     Power connection:   Fixed power supply cord with safety plug     Cable construction:   3 x 0,75 mm² H05VV-F     Cable length:   Approx. 0,9 m     Base:   Wires     Cooling:   Passive convection cooling     Control:   Plug and play     Housing color:   Black     Attachment system:   Mounting bracket     Output:   6.4V AC;     Dimensions:   Length: 16 cm     Width: 15,5 cm     Height: 17 cm     Weight:   1 kg     Motor for color wheel     Power supply:   230 V AC, 50 Hz     Power consumption:   IP20     Protection class:   Protection class I     Power connection:   Fixed power supply cord with safety plug     Cable construction:   3 x 0,75 mm² H05VV-F	Spotlight	
Protection class:	Power supply:	230 V AC, 50 Hz
Protection class:  Suitable lamp:  Max. 6,4 V/30 W PAR-36 G-53 STC  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 0,9 m  Base:  Wires  Cooling:  Passive convection cooling  Control:  Plug and play  Housing color:  Black  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class I  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Power consumption:	Max. 30 W
Suitable lamp:  Max. 6,4 V/30 W PAR-36 G-53 STC  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 0,9 m  Base:  Wires  Cooling:  Passive convection cooling  Control:  Plug and play  Housing color:  Black  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	IP classification:	IP20
Power connection:  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 0,9 m  Base:  Wires  Cooling:  Passive convection cooling  Control:  Plug and play  Housing color:  Black  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  IP classification:  IP20  Protection class:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Protection class:	Protection class I
Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 0,9 m  Base:  Wires  Cooling:  Passive convection cooling  Control:  Plug and play  Housing color:  Black  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Suitable lamp:	Max. 6,4 V/30 W PAR-36 G-53 STC
Cable length:  Base:  Wires  Cooling:  Passive convection cooling  Control:  Plug and play  Housing color:  Black  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class:  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Power connection:	Fixed power supply cord with safety plug
Base: Wires  Cooling: Passive convection cooling  Control: Plug and play  Housing color: Black  Attachment system: Mounting bracket  Output: 6.4V AC;  Dimensions: Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power supply: 230 V AC, 50 Hz  Power consumption: 4 W  IP classification: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F	Cable construction:	3 x 0,75 mm² H05VV-F
Cooling: Passive convection cooling  Control: Plug and play  Housing color: Black  Attachment system: Mounting bracket  Output: 6.4V AC;  Dimensions: Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power supply: 230 V AC, 50 Hz  Power consumption: 4 W  IP classification: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F	Cable length:	Approx. 0,9 m
Control:  Plug and play  Housing color:  Black  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class:  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Base:	Wires
Housing color:  Attachment system:  Mounting bracket  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class:  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Cooling:	Passive convection cooling
Attachment system:  Output:  6.4V AC;  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class:  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Control:	Plug and play
Output:  Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Housing color:	Black
Dimensions:  Length: 16 cm Width: 15,5 cm Height: 17 cm  Weight:  1 kg  Motor for color wheel  Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Attachment system:	Mounting bracket
Width: 15,5 cm Height: 17 cm  Weight: 1 kg  Motor for color wheel  Power supply: 230 V AC, 50 Hz  Power consumption: 4 W  IP classification: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F	Output:	6.4V AC;
Motor for color wheel  Power supply: 230 V AC, 50 Hz  Power consumption: 4 W  IP classification: IP20  Protection class: Protection class I  Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F	Dimensions:	Width: 15,5 cm
Power supply:  230 V AC, 50 Hz  Power consumption:  4 W  IP classification:  IP20  Protection class:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Weight:	1 kg
Power consumption:  IP classification:  IP20  Protection class:  Protection class I  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Motor for color wheel	
IP classification:  Protection class:  Power connection:  Fixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Power supply:	230 V AC, 50 Hz
Protection class:  Power connection:  Pixed power supply cord with safety plug  Cable construction:  3 x 0,75 mm² H05VV-F	Power consumption:	4 W
Power connection: Fixed power supply cord with safety plug  Cable construction: 3 x 0,75 mm² H05VV-F	IP classification:	IP20
Cable construction: 3 x 0,75 mm² H05VV-F	Protection class:	Protection class I
	Power connection:	Fixed power supply cord with safety plug
Cable length: Approx. 0,9 m	Cable construction:	3 x 0,75 mm² H05VV-F
	Cable length:	Approx. 0,9 m

Speed:	2,5 RPM
Control:	Plug and play
Maximum load:	1 kg
Housing color:	Black
Dimensions:	Length: 10 cm Height: 7,5 cm
Weight:	300 g
Lamp clamping ring	
Material:	Metal
Color:	Silver