

## EUROLITE LED MFX-3 Action Cube

Moving Effect with 6 light beams and Mood Light strips on the edges

Art. No.: 50944303

GTIN: 4026397576443



**The article is no longer in our assortment.**

### Features:

- Beam effect with 6 lenses and 10 W quadcolor LEDs in RGBW colors and 12 LED mood light strips with 4 RGB SMD LEDs each
- Compact lightweight
- With infinity function for unlimited TILT movement
- Positioning within 630° PAN and 200° TILT
- PAN-angle switchable between 630° and 540°
- Functions: Colored beams, LED mood light strips, auto mode, color presets, color change, Master/Slave function, built-in programs, stepless RGBW color mixture
- Masterdimmer
- Strobe effect with 1-25 flashes per second and with adjustable speed
- Random strobe effect
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- 48 powerful LEDs 0,2 W SMD 2835 3in1 TCL RGB (homogenous color mix)
- 6 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Multi beam effect
- Control via DMX; stand-alone; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 9°

### Logistic

EAN / GTIN: 4026397576443  
Weight: 6,35 kg  
Length: 0.42 m  
Width: 0.34 m  
Height: 0.27 m

**Package contents**

- 1 x omega bracket

**Technical specifications:**

|                        |   |
|------------------------|---|
| Power supply:          | 100-240 V AC, 50/60 Hz  |
| Power consumption:     | 75 W  |
| IP classification:     | IP20  |
| Power connection:      | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                    |
| Power output:          | 1 x IEC connector (F) mounting version  |
| Lamp type:             | LED lamp  |
| LED:                   | 48 x 0,2 W SMD 2835 3in1 TCL RGB (homogenous color mix)<br>6 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement:    | 200° Positioning plus infinity Auto position correction (feedback)  |
| Max. PAN movement:     | 540°, 630° Positioning Auto position correction (feedback)  |
| Flash rate:            | 0 - 25 Hz   |
| DMX channels:          | 14; 16  |
| DMX input:             | 1 x 3-pin XLR (M) mounting version  |
| DMX output:            | 1 x 3-pin XLR (F) mounting version  |
| Control:               | DMX; stand-alone; Sound to light via Microphone   |
| Preprogrammed in:      | Light'J; LED PC-Control 512; Light Captain  |
| Projection:            | Flicker-free  |
| Beam angle:            | 9°  |
| Beam angle (1/2 peak): | 9°  |
| Housing color:         | Black   |
| Dimensions:            | Width: 25 cm<br>Depth: 18 cm<br>Height: 35 cm   |
| Weight:                | 5,35 kg   |
| Legal specifications   |   |
| Special product:       | Not designed for household room illumination  |
| Intended use:          | Show effect lighting  |