

## ANTARI DarkFX Drive 4

DMX control unit for a total of 4 Antari DarkFX Strips or DarkFX Spots

Art. No.: 51100818

GTIN: 4719850658052



### Description:

The Antari DarkFX Drive 4 is a compact driver exclusively designed for the Antari DarkFX high-power UV fixtures.

Equipped with 4 bare wire terminal blocks for up to 4 fixtures, it can be used to adjust dimmer brightness and strobe speed.

The DarkFX Drive 4 is operated in one of two modes: Either in DMX mode with 2 channels via the 5-pin XLR connectors or in stand-alone mode via the LCD display and the 4 operating buttons. Use the powerCON input to connect it to the mains.

### Logistic

EAN / GTIN: 4719850658052

Weight: 2,24 kg

Length: 0.28 m

Width: 0.24 m

Height: 0.17 m

### Features:

- Terminal blocks support four fixtures
- Dimmer curves adjustable
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Built with NEUTRIK connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 75 W

IP classification: IP20

Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray)
DMX channels:	2
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Housing color:	Black
Use of brands:	Built with NEUTRIK connector
Material:	Metal
Dimensions:	Width: 13.5 cm Depth: 21.6 cm Height: 7.2 cm
Weight:	1.81 kg

### Scope of delivery:

---

1 x device  
1 x power cord  
1 x user manual