

EUROLITE N-130 Tour Fogger

1300W touring fog machine built into a durable case

Art. No.: 51702065

GTIN: 4026397668001



List price: 712.81 €

incl. 19% VAT.

Description:

Touring fog machine in case with 1300 Watt

Create a mysterious atmosphere on your stage with the EUROLITE N-130 Tour Fogger - or use the Fogger for large live events, discotheques, theatres or TV and film productions to increase the effect of your spotlights and laser beams.

Thanks to its compact dimensions and integration in the flightcase, the fog machine is also ideal for mobile events. The stable case of the fogger also ensures high resistance and durability. Addressing and setting can be done via the control unit with LCD display.

The built-in "Instant Stop" of the fog machine ensures that no more fog escapes when the fog function is switched off. The innovative quick release system allows you to quickly and easily disconnect the fluid hose from the canister and remove the tank.

You can control the device via timer, DMX or in operate it in stand-alone mode.

The EUROLITE N-130 is operated with conventional water-based fog fluid.

Logistic

EAN / GTIN: 4026397668001

Weight: 16,60 kg

Length: 0.53 m

Width: 0.45 m

Height: 0.33 m

Features:

- Integration in a stackable flightcase makes the machine tough, durable and easy to carry
- Timer with interval, duration and output volume
- Instant stop feature allows for precise output control without any sputtering
- Auto temperature control
- Fluid hose easily removable via quick connector
- Output distance: Horizontal approx. 6 m
- Output distance: Vertical approx. 5 m

- Control via DMX; stand-alone; Timer
- For application areas such as: Stage; theater; Rental; mobile djs / entertainer
- Operates on water-based fluid
- Removable tank
- Preprogrammed in Light Captain
- Application possibility: Standing

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x container, 1 x tube

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1350 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Warm-up time:	Approx. 5 min
Output volume:	Approx. 510 m³/min
Output distance:	Vertical approx. 5 m Horizontal approx. 6 m
Tank capacity:	3,5 l water-based fluid removable tank
Fluid consumption:	Approx. 100 ml/min
DMX channels:	1
DMX input:	1 x 5-pin XLR (M) mounting version 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version
Control:	DMX; stand-alone; Timer
Preprogrammed in:	Light Captain
Housing color:	Black
Heater:	1300 W
Controls:	Low fluid
Color:	Black
Dimensions:	Width: 39 cm Depth: 46 cm Height: 26,5 cm
Weight:	15,25 kg
Noise classification:	Class 2 (slight noise)