

# **ANTARI CH-1 Hazer**

Silent CO2 hazer for smooth and very long-lasting haze











# List price: 5353.81 €

incl. 19% VAT.

#### Features:

- Ideal for filming or applications where silence is crucial
- Produces large amounts of smooth haze with a very long hang time
- No pump or compressor comes built-in
- Adjustable output angle
- Timer function
- Operates on oil-based fluid
- Control via DMX; W-DMX by wireless solution (optional); timer
- TFT display
- For application areas such as: Stage; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Standing
- Package contents
- 1 x device, 1 x user manual, 1 x power cord, 1 x tube, 1 x adapter

## **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	1250 W
IP classification:	IP20
Power connection:	Mains input via PowerCON TRUE (M) mounting version power supply cord with safety plug (provided)
Warm-up time:	Approx. 8 min

### Logistic

EAN / GTIN: 4710586554076 Weight: 20,45 kg Length: 0.68 m Width: 0.28 m Heigth: 0.44 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Tank capacity:	2,5 I oil-based fluid fixed tank
Fluid consumption:	Approx. 2 ml/min at 2,78 bar
Gas type:	CO2; N2
Gas pressure range:	3,4 - 4,1 bar
Gas consumption:	0,36 kg/h at 2,76 bar
	0,18 kg/h at 1,38 bar
DMX channels:	1; 3; 5
DMX input:	3-pin XLR (M) mounting version
	5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
	5-pin XLR (F) mounting version
Control:	DMX; W-DMX by wireless solution (optional); timer
Housing color:	Grey
Display type:	TFT display
Color:	Grey
Dimensions:	Length: 57,9 cm
	Width: 16,4 cm
	Height: 31,1 cm
Weight:	18,30 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)