

## EUROLITE Confetti Double Shot DMX

Electric firing unit with 2 channels and DMX control for confetti and streamers

Art. No.: 51707831

GTIN: 4026397738155



### Description:

Confetti Double Shot DMX is a compact firing unit for confetti or streamer cannons of various brands. Two confetti and streamer cannons can be fired simultaneously or individually at the push of a button or via DMX signal. An additional safety channel prevents misfires in DMX mode. The projection angles of both cannons can be independently adjusted by 180° and rotated by 90°. The base plate provides a secure footing and M10 flying points for flexible mounting options.

### Logistic

EAN / GTIN: 4026397738155

Weight: 8,90 kg

Length: 0.38 m

Width: 0.34 m

Height: 0.22 m

### Features:

- The electric shooter can be used for confetti or streamer cannons
- Fires 2 cannons simultaneously or individually
- Suitable for electric cannons with 50 and 80 cm length
- The shooting angle can be adjusted steplessly
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Standing; suspended

## Technical specifications:

---

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 110 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, F 3 A fuse replaceable
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Housing color:	Black matte
Display type:	Monochrome LCD display
USB port:	1 x type A
Diameter mounting holes:	4 x Ø10mm
Use of brands:	Built with SEETRONIC connector
Material:	Metal, painted
Dimensions:	Length: 32.5 cm Width: 26.5 cm Height: 20 cm
Weight:	8.30 kg

## Scope of delivery:

---

1 x device  
1 x user manual  
1 x power cord