

## EUROLITE LED Laser Slim FX Spot

Flat PAR spotlight with additional RG laser (2M) and strobe

Art. No.: 51741074

GTIN: 4026397620801



**The article is no longer in our assortment.**

### Features:

- 6 high-power 4 W 4in1 LEDs for RGBW wash effects
- 12 cold white 0.5 W SMD LEDs for fast, dynamic strobe effects
- 2 laser diodes project thousands of red and green laser beams
- Laser class 2M: does not require additional protective measures or appointment of a laser safety officer
- Spotlight, laser and strobe can be controlled individually
- Auto, music, master/slave and DMX mode
- Silent operation
- 7 built-in auto and music show programs
- Direct color selection for 20 preset colors
- Stepless color mixture, color change, color fade, dimmer and strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Sound-control via built-in microphone with adjustable microphone sensitivity
- DMX512 control possible via any commercial DMX controller
- 2, 3, 4, 6, 10, or 14 DMX channels selectable for various applications
- Swivel mounting bracket
- Additional bracket for floor use
- Feed-through output allows to power up to 8 devices
- 12 powerful LEDs 0,5 W SMD 5050 cold white (CW)
- 6 powerful LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone

### Logistic

EAN / GTIN: 4026397620801  
Weight: 2,07 kg  
Length: 0.30 m  
Width: 0.28 m  
Height: 0.16 m

- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 25°

**Package contents**

- 1 x remote control

**Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	12 x 0,5 W SMD 5050 cold white (CW) 6 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 50 mW 532nm Red (R) 100 mW 650nm
DMX channels:	2; 3; 4; 6; 10; 14
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Dimensions:	Width: 26,5 cm Depth: 10 cm Height: 21 cm
Weight:	1,73 kg
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
LEDs	
Wash effect:	6 x RGBW (4in1), 4 W each
Strobe effect:	12 x white, 0.5 W each
DMX connection:	3-pin XLR
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting