

EUROLITE LED Laser Derby MK2

DMX light effect with RG laser (2M), rotating LED derby, stroboscope and IR remote control

Art. No.: 51741079

GTIN: 4026397690019



Features:

- 2 laser diodes project hundreds of red and green laser beams
 - Dimmer electronic; color macros adjustable
 - Laser; multi beam effect; strobe effect
 - 7 integrated show programs
 - The device is cooled by cooling fan
 - Control via IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
 - Fixtures available for Light Captain; EASY SHOW 2; Colorchief
 - With mounting bracket
 - 4 digit 7-segment LED display
 - For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
 - Application possibility: Suspended; on stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- light effect**
- 4 LEDs 10 W SMD 5050 R/G/B/W
- strobes**
- 16 LEDs 0.6 W SMD 2835 cold white (CW)

Logistic

EAN / GTIN: 4026397690019

Weight: 2,50 kg

Length: 0.31 m

Width: 0.27 m

Height: 0.20 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC (M) power supply cord with safety plug
Power output:	IEC connector (F) mounting version Bypass
Fuse:	5 x 20 mm, T 1.6 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	2; 4; 5; 6; 8; 7; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; Colorchief
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Control elements:	Navigation keys, sensitivity rotary dial
Status LED:	DMX, slave mode, auto mode, sound mode
Dimensions:	Width: 26 cm Depth: 19 cm Height: 19 cm
Weight:	2.17 kg
Cable length:	1.5 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 35 mW 532nm Red (R) 100 mW 650nm
LED type:	4 x 10 W SMD 5050 R/G/B/W
LED type:	16 x 0.6 W SMD 2835 cold white (CW)

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x mounting bracket
- 2 x knurled screw
- 2 x washer