

EUROLITE LED FE-2500 Hypno Hybrid Laser Effect

LED effect light with threefold effects: RGB+UV washlight, 3 hypno rings and laser (2M)

Art. No.: 51741084

GTIN: 4026397642780



The article is no longer in our assortment.

Features:

- 12 high-power 8 W RGB+UV LEDs (4in1) subdivided into 6 pixels for washlight and blacklight effects
 - 3 concentric hypno rings with altogether 75 RGB LEDs provide psychedelic ring effects
 - 2 laser diodes for of red and green star laser effects
 - Laser class 2M: does not require additional protective measures or appointment of a laser safety officer
 - All effects can be controlled individually
 - 8 built-in auto and music show programs
 - Direct color selection for 17 preset colors
 - Addressing and setting via control panel with 4-digit LED display
 - Convenient wireless control via included IR remote control EUROLITE IR-7
 - Supports QuickDMX - the wireless DMX system from Eurolite
 - Built-in phantom-powered USB port for QuickDMX receivers (accessories)
 - Swivel mounting bracket
 - IEC terminals for power linking up to 8 units
 - Switch-mode power supply for operation between 100 and 240 volts
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; Light J
 - With a beam angle of 25°
 - Very quiet working noise
- laser**
- Laser

Logistic

EAN / GTIN: 4026397642780

Weight: 4,70 kg

Length: 0.35 m

Width: 0.35 m

Height: 0.24 m

- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 12 powerful LEDs 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- UV effect
- light effect**
- 76 powerful LEDs 0,5 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- Package contents**
- 1 x remote control

Technical specifications:

| | |
|------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 70 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| DMX channels: | 11; 16; 18; 36 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | LED PC-Control 512; EASY SHOW 1; Light Captain; Light J |
| Beam angle: | 25° |
| Beam angle (1/2 peak): | 25° |
| Housing color: | Black |
| Dimensions: | Width: 32,6 cm Depth: 21,7 cm Height: 31,9 cm |
| Weight: | 4,10 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Laser | |
| Laser class: | 2M |
| Laser color: | R/G |
| Laser module: | Red (R) 100 mW 650nm Green (G) 50 mW 532nm |
| Spotlight | |
| LED: | 12 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix) |
| Light effect | |

| | |
|----------------|--|
| LED: | 76 x 0,5 W SMD 5050 3in1 TCL RGB (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |