

EUROLITE LED Compact Multi FX Laser Bar

4in1 light effect with LED matrix, blacklight, RG laser and stroboscope

Art. No.: 51741098

GTIN: 4026397701852



Features:

- 2 laser diodes project hundreds of red and green laser beams
- Matrix, blacklight, laser and strobe can be controlled individually
- 14 integrated show programs
- The device is cooled by cooling fan
- Control via DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain; Light´J
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Very quiet working noise
- Application possibility: Suspended; standing; on stand
- laser**
- Laser
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 2 LEDs 3 W high-power ultra violet (UV)
- UV effect
- light effect**
- 128 LEDs 5 mm R/G/B/W/A
- Flower effect; multi beam effect
- strobes**

Logistic

EAN / GTIN: 4026397701852

Weight: 3,30 kg

Length: 0.46 m

Width: 0.19 m

Height: 0.22 m

- 24 LEDs 0.5 W SMD 5030 cold white (CW)
- Strobe effect

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	2; 5; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; Light J
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Length: 40.5 cm Depth: 14.75 cm Height: 20 cm
Weight:	2.85 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	2 x 3 W high-power ultra violet (UV)
LED type:	128 x 5 mm R/G/B/W/A
LED type:	24 x 0.5 W SMD 5030 cold white (CW)
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm

Scope of delivery:

- 1 x remote control
- 1 x battery
- 1 x device
- 1 x user manual
- 1 x power cord