

LASERWORLD EL-500RGB KeyTEX

RGB text projection laser (500 mW), with keyboard & infrared remote control

Art. No.: 51743205

GTIN: 7640144992217



The article is no longer in our assortment.

Description:

The Laserworld EL-500RGB KeyTEX is a RGB text and pattern projection laser that does not need any software or additional controller for operation. It comes with a special keyboard and an infrared remote control.

With the keyboard it is possible to control the whole show laser light system.

This text laser is equipped with a strong red (650 nm, 180 mW), green (532 nm DPSS, 80 mW) and blue (445 nm, 160 mW) laser source, so the projections are well visible. The scanning systems allows for simple text projections and runs at ca. 15kpps@4°.

The mounting bracket of the EL-500RGB KeyTEX laser can be used to mount the projector at walls, ceilings or at other appropriate objects.

Features:

- Write texts live with the keyboard
- Save texts and recall them later
- Animate the texts: scrolling, flipping, typing of single letters, rotations and many more features available through the keyboard
- Trigger saved texts with infrared remote control
- Play the preset patterns and effects in automatic mode or sound mode - this can be switched with the keyboard or the infrared remote control
- Clock feature: set time and project it on any surface
- The projection (texts, patterns) can be multiplied through a diffraction grating at the laser aperture
- Controllable via DMX
- RGB projections
- Included in delivery are:

Logistic

EAN / GTIN: 7640144992217

Weight: 2,75 kg

Length: 0.32 m

Width: 0.25 m

Height: 0.19 m

- EL-500RGB KeyTEX laser projector
- Keyboard for EL-500RGB KeyTEX
- USB extension cable for keyboard
- Infrared remote control
- Interlock adapter
- Keys for the key switch
- External power supply
- Control via stand-alone; DMX; IR remote control; Sound to light

Package contents

- 1 x remote control, 1 x laser, 1 x external mains adapter, 1 x user manual, 1 x key, 1 x interlock

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version
Laser class:	3B
Laser color:	R/G/B
Laser module:	Red (R) 180 mW 650nm Green (G) 80 mW 532nm Blue (B) 160 mW 445nm
Control:	Stand-alone; DMX; IR remote control; Sound to light
Housing color:	Black
Dimensions:	Width: 16,5 cm Depth: 21 cm Height: 8,5 cm
Weight:	1,64 kg