

## EUROLITE LED TMH-W36 Moving Head Zoom Wash

Washlight with 4 x 9 W LEDs, 4in1 QCL RGBW color mixing and motorized zoom

Art. No.: 51785880

GTIN: 4026397693492



### Features:

- 4 LEDs 9 W high-power 4in1 QCL RGBW (homogenous color mix)
- Positioning within 540° PAN, 220° TILT
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Motion macros adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light´J; GDTF (GrandMA3)
- Flicker-free
- With a beam angle of 6° - 40°
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; small rental
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397693492

Weight: 3,40 kg

Length: 0.29 m

Width: 0.22 m

Height: 0.28 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	65 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 1.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	4 x 9 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	220° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Equipment:	Zoom motor driven
DMX channels:	15
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; GDTF (GrandMA3)
Projection:	Flicker-free
Beam angle:	6° - 40°
Beam angle (1/2 peak):	6 - 25°
Beam angle (1/10 peak):	10 - 40°
Illuminance in Lux (lx):	Narrow red (R) 1m: 6781 lx, 3m: 747 lx, 6m: 192 lx Narrow green (G) 1m: 12971 lx, 3m: 1381 lx, 6m: 348 lx Narrow blue (B) 1m: 2238 lx, 3m: 290 lx, 6m: 73 lx Narrow cold white (CW) 1m: 16580 lx, 3m: 1864 lx, 6m: 456 lx Narrow all 1m: 36301 lx, 3m: 4064 lx, 6m: 1011 lx Wide red (R) 1m: 746 lx, 3m: 85 lx, 6m: 24 lx Wide green (G) 1m: 1343 lx, 3m: 164 lx, 6m: 44 lx Wide blue (B) 1m: 291 lx, 3m: 35 lx, 6m: 10 lx Wide cold white (CW) 1m: 1852 lx, 3m: 214 lx, 6m: 58 lx Wide all 1m: 4023 lx, 3m: 471 lx, 6m: 127 lx
Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 15.5 cm Depth: 14.5 cm Height: 25.5 cm
Weight:	2.95 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

---

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x safety eyelet